

BERKELEY LOGO

Berkeley Logo User Manual

Brian Harvey

1 Introduction

1.1 Overview

Copyright © 1993 by the Regents of the University of California

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but *WITHOUT ANY WARRANTY*; without even the implied warranty of *MERCHANTABILITY* or *FITNESS FOR A PARTICULAR PURPOSE*. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

This is a program that is still being written. Many things are missing, including adequate documentation. This manual assumes that you already know how to program in Logo, and merely presents the details of this new implementation.

Read `Computer_Science_Logo_Style, Volume_1:_Symbolic_Computing_` by Brian Harvey (MIT Press, 1997) for a tutorial on Logo programming with emphasis on symbolic computation.

Here are the special features of this dialect of Logo:

Source file compatible among Unix, DOS, Windows, and Mac platforms.

Random-access arrays.

Variable number of inputs to user-defined procedures.

Mutators for list structure (dangerous).

Pause on error, and other improvements to error handling.

Comments and continuation lines; formatting is preserved when procedure definitions are saved or edited.

Terrapin-style tokenization (e.g., `[2+3]` is a list with one member) but LCSI-style syntax (no special forms except `TO`). The best of both worlds.

First-class instruction and expression templates (see `APPLY`).

Macros.

Features **not** found in Berkeley Logo include robotics, music, GUIs, animation, parallelism, and multimedia. For those, buy a commercial version.

1.2 Getter/Setter Variable Syntax

Logo distinguishes *PROCEDURES* from *VARIABLES*. A procedure is a set of instructions to carry out some computation; a variable is a named container that holds a data value such as a number, word, list, or array.

In traditional Logo syntax, a non-numeric word typed without punctuation represents a request to invoke the procedure named by that word. A word typed with a preceding quotation mark represents the word itself. For example, in the instruction

```
PRINT FIRST "WORD
```

the procedures named **FIRST** and **PRINT** are invoked, but the procedure named *WORD* is not invoked; the word *W-O-R-D* is the input to **FIRST**.

What about variables? There are two things one can do with a variable: give it a value, and find out its value. To give a variable a value, Logo provides the primitive procedure **MAKE**, which requires two inputs: the name of the variable and the new value to be assigned. The first input, the name of the variable, is just a word, and if (as is almost always the case) the programmer wants to assign a value to a specific variable whose name is known in advance, that input is quoted, just as any known specific word would be:

```
MAKE "MY.VAR FIRST "WORD
```

gives the variable named *MY.VAR* the value *W* (the first letter of *WORD*).

To find the value of a variable, Logo provides the primitive procedure **THING**, which takes a variable name as its input, and outputs the value of the accessible variable with that name. Thus

```
PRINT THING "MY.VAR
```

will print *W* (supposing the **MAKE** above has been done). Since finding the value of a specific, known variable name is such a common operation, Logo also provides an abbreviated notation that combines **THING** with quote:

```
PRINT :MY.VAR
```

The colon (which Logo old-timers pronounce "dots") replaces **THING** and **"** in the earlier version of the instruction.

Newcomers to Logo often complain about the need for all this punctuation. In particular, Logo programmers who learned about dots and quotes without also learning about **THING** wonder why an instruction such as

```
MAKE "NEW.VAR :OLD.VAR
```

uses two different punctuation marks to identify the two variables. (Having read the paragraphs above, you will understand that actually both variable names are quoted, but the procedure **THING** is invoked to find the value of *OLD.VAR*, since it's that value, not *OLD.VAR*'s

name, that **MAKE** needs to know. It wouldn't make sense to ask for **THING** of *NEW.VAR*, since we haven't given *NEW.VAR* a value yet.)

Although Logo's punctuation rules make sense once understood, they do form a barrier to entry for the Logo beginner. Why, then, couldn't Logo be designed so that an unpunctuated word would represent a procedure if there is a procedure by that name, or a variable if there is a variable by that name? Then we could say

```
PRINT MY.VAR
```

and Logo would realize that *MY.VAR* is the name of a variable, not of a procedure. The traditional reason not to use this convention is that Logo allows the same word to name a procedure and a variable at the same time. This is most often important for words that name data types, as in the following procedure:

```
TO PLURAL :WORD
  OUTPUT WORD :WORD "S
END
```

Here the name *WORD* is a natural choice for the input to **PLURAL**, since it describes the kind of input that **PLURAL** expects. Within the procedure, we use **WORD** to represent Logo's primitive procedure that combines two input words to form a new, longer word; we use **:WORD** to represent the variable containing the input, whatever actual word is given when **PLURAL** is invoked.

```
? PRINT PLURAL "COMPUTER
COMPUTERS
```

However, if a Logo instruction includes an unquoted word that is **not** the name of a procedure, Logo could look for a variable of that name instead. This would allow a "punctuationless" Logo, *** PROVIDED THAT USERS WHO WANT TO WORK WITHOUT COLONS FOR VARIABLES CHOOSE VARIABLE NAMES THAT ARE NOT ALSO PROCEDURE NAMES. ***

What about assigning a value to a variable? Could we do without the quotation mark on **MAKE**'s first input? Alas, no. Although the first input to **MAKE** is **usually** a constant, known variable name, sometimes it isn't, as in this example:

```
TO INCREMENT :VAR
  MAKE :VAR (THING :VAR)+1 ; Note: it's not "VAR here!
END

? MAKE "X 5
? INCREMENT "X
? PRINT :X
6
```

The procedure **INCREMENT** takes a variable name as its input and changes the value of that variable. In this example there are two variables; the variable whose name is *VAR*, and whose value is the word *X*; and the variable whose name is *X* and whose value changes from 5 to 6. Suppose we changed the behavior of **MAKE** so that it took the word after **MAKE** as the name of the variable to change; we would be unable to write **INCREMENT**:

```

TO INCREMENT :VAR
MAKE VAR (THING VAR)+1
END

```

This would assign a new value to *VAR*, not to *X*.

What we can do is to allow an **alternative** to **MAKE**, a "setter" procedure for a particular variable. The notation will be

```

? SETFOO 7
? PRINT FOO
7

```

SETFOO is a "setter procedure" that takes one input (in this case the input 7) and assigns its value to the variable named *FOO*.

Berkeley Logo allows users to choose either the traditional notation, in which case the same name can be used both for a procedure and for a variable, or the getter/setter notation, in which variable *FOO* is set with **SETFOO** and examined with *FOO*, but the same name can't be used for procedure and variable.

Here is how this choice is allowed: Berkeley Logo uses traditional notation, with procedures distinct from variables. However, if there is a variable named *AllowGetSet* whose value is **TRUE** (which there is, by default, when Logo starts up), then if a Logo instruction refers to a **nonexistent** procedure (so that the error message "I don't know how to ..." would result), Logo tries the following two steps:

1. If the name is at least four characters long, and the first three characters are the letters **SET** (upper or lower case), and if the name is followed in the instruction by another value, and if the name without the **SET** is the name of a variable that already exists, then Logo will invoke **MAKE** with its first input being the name without the **SET**, and its second input being the following value.
2. If step 1's conditions are not met, but the name is the name of an accessible variable, then Logo will invoke **THING** with that name as input, to find the variable's value.

Step 1 requires that the variable already exist so that misspellings of names of **SETxxx** primitives (e.g., **SETHEADING**) will still be caught, instead of silently creating a new variable. The command **GLOBAL** can be used to create a variable without giving it a value.

One final point: The **TO** command in Logo has always been a special case; the rest of the line starting with **TO** is not evaluated as ordinary Logo expressions are. In particular, the colons used to mark the names of inputs to the procedure do not cause **THING** to be invoked. They are merely mnemonic aids, reminding the Logo user that these words are names of variables. (Arguably, this nonstandard behavior of **TO** adds to Logo beginners' confusion about colons.) To a programmer using colonless variable references, the colons in the **TO** line are unnecessary and meaningless. Berkeley Logo therefore makes the colons optional:

```

TO FOO :IN1 :IN2

```

and

TO FOO IN1 IN2

are both allowed.

1.3 Entering and Leaving Logo

The process to start Logo depends on your operating system:

- ‘Unix:’ Type the word `logo` to the shell. (The directory in which you’ve installed Logo must be in your path.)
- ‘DOS:’ Change directories to the one containing Logo (probably `C:\UCBLOGO`). Then type `UCBLOGO` for the large memory version, or `BL` for the 640K version.
- ‘Mac:’ Double-click on the LOGO icon within the "UCB Logo" folder.
- ‘Windows:’ Double-click on the UCBWLOGO icon in the UCBLOGO folder.

To leave Logo, enter the command `bye`.

Under Unix, DOS, or Windows, if you include one or more filenames on the command line when starting Logo, those files will be loaded before the interpreter starts reading commands from your terminal. If you load a file that executes some program that includes a `BYE` command, Logo will run that program and exit. You can therefore write standalone programs in Logo and run them with shell/batch scripts. To support this technique, Logo does not print its usual welcoming and parting messages if you give file arguments to the `logo` command.

If you type your interrupt character (see table below) Logo will stop what it’s doing and return to top-level, as if you did `THROW "TOPLEVEL`. If you type your quit character Logo will pause as if you did `PAUSE`.

	Unix	DOS/Windows	Mac
<code>toplevel</code>	usually <code>ctrl-C</code>	<code>ctrl-Q</code>	<code>command-.</code> (period)
<code>pause</code>	usually <code>ctrl-\</code>	<code>ctrl-W</code>	<code>command-,</code> (comma)

If you have an environment variable called `LOGOLIB` whose value is the name of a directory, then Logo will use that directory instead of the default library. If you invoke a procedure that has not been defined, Logo first looks for a file in the current directory named `proc.lg` where `proc` is the procedure name in lower case letters. If such a file exists, Logo loads that file. If the missing procedure is still undefined, or if there is no such file, Logo then looks in the library directory for a file named `proc` (no `.lg`) and, if it exists, loads it. If neither file contains a definition for the procedure, then Logo signals an error. Several procedures that are primitive in most versions of Logo are included in the default library, so if you use a different library you may want to include some or all of the default library in it.

1.4 Tokenization

Names of procedures, variables, and property lists are case-insensitive. So are the special words END, TRUE, and FALSE. Case of letters is preserved in everything you type, however.

Within square brackets, words are delimited only by spaces and square brackets. [2+3] is a list containing one word. Note, however, that the Logo primitives that interpret such a list as a Logo instruction or expression (RUN, IF, etc.) reparses the list as if it had not been typed inside brackets.

After a quotation mark outside square brackets, a word is delimited by a space, a square bracket, or a parenthesis.

A word not after a quotation mark or inside square brackets is delimited by a space, a bracket, a parenthesis, or an infix operator +-*/=<>. Note that words following colons are in this category. Note that quote and colon are not delimiters.

A word consisting of a question mark followed by a number (e.g., ?37), when runparsed (i.e., where a procedure name is expected), is treated as if it were the sequence

(? 37)

making the number an input to the ? procedure. (See the discussion of templates, below.) This special treatment does not apply to words read as data, to words with a non-number following the question mark, or if the question mark is backslashed.

A line (an instruction line or one read by READLIST or READWORD) can be continued onto the following line if its last character is a tilde (~). READWORD preserves the tilde and the newline; READLIST does not.

Lines read with READRAWLINE are never continued.

An instruction line or a line read by READLIST (but not by READWORD) is automatically continued to the next line, as if ended with a tilde, if there are unmatched brackets, parentheses, braces, or vertical bars pending. However, it's an error if the continuation line contains only the word END; this is to prevent runaway procedure definitions. Lines explicitly continued with a tilde avoid this restriction.

If a line being typed interactively on the keyboard is continued, either with a tilde or automatically, Logo will display a tilde as a prompt character for the continuation line.

A semicolon begins a comment in an instruction line. Logo ignores characters from the semicolon to the end of the line. A tilde as the last character still indicates a continuation line, but not a continuation of the comment. For example, typing the instruction

```
print "abc;comment ~
def
```

will print the word abcdef. Semicolon has no special meaning in data lines read by READWORD or READLIST, but such a line can later be reparsed using RUNPARSE and then comments will be recognized.

To include an otherwise delimiting character (including semicolon or tilde) in a word, precede it with backslash (\). If the last character of a line is a backslash, then the newline character following the backslash will be part of the last word on the line, and the line continues onto the following line. To include a backslash in a word, use \\. If the combination backslash-newline is entered at the terminal, Logo will issue a backslash as a prompt character for the continuation line. All of this applies to data lines read with READWORD or READLIST as well as to instruction lines. A character entered with backslash is EQUALP to the same character without the backslash, but can be distinguished by the BACKSLASHEDP predicate. (However, BACKSLASHEDP recognizes backslashedness only on characters for which it is necessary: whitespace, parentheses, brackets, infix operators, backslash, vertical bar, tilde, quote, question mark, colon, and semicolon.)

A line read with READRAWLINE has no special quoting mechanism; both backslash and vertical bar (described below) are just ordinary characters.

An alternative notation to include otherwise delimiting characters in words is to enclose a group of characters in vertical bars. All characters between vertical bars are treated as if they were letters. In data read with READWORD the vertical bars are preserved in the resulting word. In data read with READLIST (or resulting from a PARSE or RUNPARSE of a word) the vertical bars do not appear explicitly; all potentially delimiting characters (including spaces, brackets, parentheses, and infix operators) appear as though entered with a backslash. Within vertical bars, backslash may still be used; the only characters that must be backslashed in this context are backslash and vertical bar themselves.

Characters entered between vertical bars are forever special, even if the word or list containing them is later reparsed with PARSE or RUNPARSE. Characters typed after a backslash are treated somewhat differently: When a quoted word containing a backslashed character is runparsed, the backslashed character loses its special quality and acts thereafter as if typed normally. This distinction is important only if you are building a Logo expression out of parts, to be RUN later, and want to use parentheses. For example,

```
PRINT RUN (SE "\ ( 2 "+ 3 "\))
```

will print 5, but

```
RUN (SE "MAKE ""|(| 2)
```

will create a variable whose name is open-parenthesis. (Each example would fail if vertical bars and backslashes were interchanged.)

2 Data Structure Primitives

2.1 Constructors

word

```
WORD word1 word2  
(WORD word1 word2 word3 ...)
```

outputs a word formed by concatenating its inputs.

list

```
LIST thing1 thing2  
(LIST thing1 thing2 thing3 ...)
```

outputs a list whose members are its inputs, which can be any Logo datum (word, list, or array).

sentence

```
SENTENCE thing1 thing2  
SE thing1 thing2  
(SENTENCE thing1 thing2 thing3 ...)  
(SE thing1 thing2 thing3 ...)
```

outputs a list whose members are its inputs, if those inputs are not lists, or the members of its inputs, if those inputs are lists.

fput

```
FPUT thing list
```

outputs a list equal to its second input with one extra member, the first input, at the beginning.

lput

```
LPUT thing list
```

outputs a list equal to its second input with one extra member, the first input, at the end.

array

```
ARRAY size  
(ARRAY size origin)
```

outputs an array of **size** members (must be a positive integer), each of which initially is an empty list. Array members can be selected with **ITEM** and changed with **SETITEM**.

The first member of the array is member number 1 unless an **origin** input (must be an integer) is given, in which case the first member of the array has that number as its index. (Typically 0 is used as the origin if anything.) Arrays are printed by PRINT and friends, and can be typed in, inside curly braces; indicate an origin with {a b c}@0.

See [ITEM], page 12 , [SETITEM], page 13 , [PRINT], page 21 .

mdarray

```
MDARRAY sizelist (library procedure)
(MDARRAY sizelist origin)
```

outputs a multi-dimensional array. The first input must be a list of one or more positive integers. The second input, if present, must be a single integer that applies to every dimension of the array.

Ex: (MDARRAY [3 5] 0) outputs a two-dimensional array whose members range from [0 0] to [2 4].

listtoarray

```
LISTTOARRAY list
(LISTTOARRAY list origin)
```

outputs an array of the same size as the input list, whose members are the members of the input list.

arraytolist

```
ARRAYTOLIST array
```

outputs a list whose members are the members of the input array. The first member of the output is the first member of the array, regardless of the array's origin.

combine

```
COMBINE thing1 thing2 (library procedure)
```

if thing2 is a word, outputs WORD thing1 thing2. If thing2 is a list, outputs FPUT thing1 thing2.

See [WORD], page 9 , [FPUT], page 9

reverse

```
REVERSE list (library procedure)
```

outputs a list whose members are the members of the input list, in reverse order.

gensym

`GENSYM` (library procedure)

outputs a unique word each time it's invoked. The words are of the form G1, G2, etc.

2.2 Data Selectors

first

`FIRST thing`

if the input is a word, outputs the first character of the word. If the input is a list, outputs the first member of the list. If the input is an array, outputs the origin of the array (that is, the INDEX OF the first member of the array).

firsts

`FIRSTS list`

outputs a list containing the FIRST of each member of the input list. It is an error if any member of the input list is empty. (The input itself may be empty, in which case the output is also empty.) This could be written as

```
to firsts :list
  output map "first :list
end
```

but is provided as a primitive in order to speed up the iteration tools `MAP`, `MAP.SE`, and `FOREACH`.

```
to transpose :matrix
  if empty? first :matrix [op []]
  op fput firsts :matrix transpose bfs :matrix
end
```

See [MAP], page 79 , [MAPdSE], page 79 , [FOREACH], page 79

last

`LAST wordorlist`

if the input is a word, outputs the last character of the word. If the input is a list, outputs the last member of the list.

butfirst

`BUTFIRST wordorlist`
`BF wordorlist`

if the input is a word, outputs a word containing all but the first character of the input. If the input is a list, outputs a list containing all but the first member of the input.

butfirsts

```
BUTFIRSTS list
BFS list
```

outputs a list containing the BUTFIRST of each member of the input list. It is an error if any member of the input list is empty or an array. (The input itself may be empty, in which case the output is also empty.) This could be written as

```
to butfirsts :list
  output map "butfirst :list
end
```

but is provided as a primitive in order to speed up the iteration tools **MAP**, **MAP.SE**, and **FOREACH**.

See [MAP], page 79 , [MAPdSE], page 79 , [FOREACH], page 79

butlast

```
BUTLAST wordorlist
BL wordorlist
```

if the input is a word, outputs a word containing all but the last character of the input. If the input is a list, outputs a list containing all but the last member of the input.

item

```
ITEM index thing
```

if the **thing** is a word, outputs the **index**th character of the word. If the **thing** is a list, outputs the **index**th member of the list. If the **thing** is an array, outputs the **index**th member of the array. **Index** starts at 1 for words and lists; the starting index of an array is specified when the array is created.

mditem

```
MDITEM indexlist array (library procedure)
```

outputs the member of the multidimensional **array** selected by the list of numbers **indexlist**.

pick

```
PICK list (library procedure)
```

outputs a randomly chosen member of the input list.

remove

```
REMOVE thing list (library procedure)
```

outputs a copy of **list** with every member equal to **thing** removed.

remdup

REMDUP list (library procedure)

outputs a copy of **list** with duplicate members removed. If two or more members of the input are equal, the rightmost of those members is the one that remains in the output.

quoted

QUOTED thing (library procedure)

outputs its input, if a list; outputs its input with a quotation mark prepended, if a word.

2.3 Data Mutators

setitem

SETITEM index array value

command. Replaces the **indexth** member of **array** with the new **value**. Ensures that the resulting array is not circular, i.e., **value** may not be a list or array that contains **array**.

mdsetitem

MDSETITEM indexlist array value (library procedure)

command. Replaces the member of **array** chosen by **indexlist** with the new **value**.

.setfirst

.SETFIRST list value

command. Changes the first member of **list** to be **value**.

WARNING: Primitives whose names start with a period are DANGEROUS. Their use by non-experts is not recommended. The use of **.SETFIRST** can lead to circular list structures, which will get some Logo primitives into infinite loops; unexpected changes to other data structures that share storage with the list being modified; and the loss of memory if a circular structure is released.

.setbf

.SETBF list value

command. Changes the butfirst of **list** to be **value**.

WARNING: Primitives whose names start with a period are DANGEROUS. Their use by non-experts is not recommended. The use of **.SETBF** can lead to circular list structures,

which will get some Logo primitives into infinite loops; unexpected changes to other data structures that share storage with the list being modified; Logo crashes and coredumps if the butfirst of a list is not itself a list; and the loss of memory if a circular structure is released.

.setitem

.SETITEM *index array value*

command. Changes the **index**th member of **array** to be **value**, like SETITEM, but without checking for circularity.

WARNING: Primitives whose names start with a period are DANGEROUS. Their use by non-experts is not recommended. The use of .SETITEM can lead to circular arrays, which will get some Logo primitives into infinite loops; and the loss of memory if a circular structure is released.

See [SETITEM], page 13.

push

PUSH *stackname thing (library procedure)*

command. Adds the **thing** to the stack that is the value of the variable whose name is **stackname**. This variable must have a list as its value; the initial value should be the empty list. New members are added at the front of the list.

pop

POP *stackname (library procedure)*

outputs the most recently PUSHed member of the stack that is the value of the variable whose name is **stackname** and removes that member from the stack.

queue

QUEUE *queueName thing (library procedure)*

command. Adds the **thing** to the queue that is the value of the variable whose name is **queueName**. This variable must have a list as its value; the initial value should be the empty list. New members are added at the back of the list.

dequeue

DEQUEUE *queueName (library procedure)*

outputs the least recently QUEUED member of the queue that is the value of the variable whose name is **queueName** and removes that member from the queue.

2.4 Predicates

wordp

```
WORDP thing
WORD? thing
```

outputs TRUE if the input is a word, FALSE otherwise.

listp

```
LISTP thing
LIST? thing
```

outputs TRUE if the input is a list, FALSE otherwise.

arrayp

```
ARRAYP thing
ARRAY? thing
```

outputs TRUE if the input is an array, FALSE otherwise.

emptyp

```
EMPTYP thing
EMPTY? thing
```

outputs TRUE if the input is the empty word or the empty list, FALSE otherwise.

equalp

```
EQUALP thing1 thing2
EQUAL? thing1 thing2
thing1 = thing2
```

outputs TRUE if the inputs are equal, FALSE otherwise. Two numbers are equal if they have the same numeric value. Two non-numeric words are equal if they contain the same characters in the same order. If there is a variable named *CASEIGNOREDP* whose value is TRUE, then an upper case letter is considered the same as the corresponding lower case letter. (This is the case by default.) Two lists are equal if their members are equal. An array is only equal to itself; two separately created arrays are never equal even if their members are equal. (It is important to be able to know if two expressions have the same array as their value because arrays are mutable; if, for example, two variables have the same array as their values then performing SETITEM on one of them will also change the other.)

See [CASEIGNOREDP], page 91 , [SETITEM], page 13

beforep

```
BEFOREP word1 word2
BEFORE? word1 word2
```


outputs TRUE if word1 comes before word2 in ASCII collating sequence (for words of letters, in alphabetical order). Case-sensitivity is determined by the value of CASEIGNOREDP. Note that if the inputs are numbers, the result may not be the same as with LESSP; for example, BEFOREP 3 12 is false because 3 collates after 1.

See [CASEIGNOREDP], page 91 , [LESSP], page 34

.eq

```
.EQ thing1 thing2
```

outputs TRUE if its two inputs are the same datum, so that applying a mutator to one will change the other as well. Outputs FALSE otherwise, even if the inputs are equal in value.

WARNING: Primitives whose names start with a period are DANGEROUS. Their use by non-experts is not recommended. The use of mutators can lead to circular data structures, infinite loops, or Logo crashes.

memberp

```
MEMBERP thing1 thing2
MEMBER? thing1 thing2
```

if **thing2** is a list or an array, outputs TRUE if **thing1** is EQUALP to a member of **thing2**, FALSE otherwise. If **thing2** is a word, outputs TRUE if **thing1** is a one-character word EQUALP to a character of **thing2**, FALSE otherwise.

See [EQUALP], page 15 .

substringp

```
SUBSTRINGP thing1 thing2
SUBSTRING? thing1 thing2
```

if **thing1** or **thing2** is a list or an array, outputs FALSE. If **thing2** is a word, outputs TRUE if **thing1** is EQUALP to a substring of **thing2**, FALSE otherwise.

See [EQUALP], page 15 .

numberp

```
NUMBERP thing
NUMBER? thing
```

outputs TRUE if the input is a number, FALSE otherwise.

backslashedp

```
BACKSLASHEDP char
BACKSLASHED? char
```

outputs TRUE if the input character was originally entered into Logo with a backslash (\) before it or within vertical bars (|) to prevent its usual special syntactic meaning, FALSE otherwise. (Outputs TRUE only if the character is a backslashed space, tab, newline, or one of () [] + - * / = < > " ; \ ~ ? |)

2.5 Queries

count

`COUNT thing`

outputs the number of characters in the input, if the input is a word; outputs the number of members in the input, if it is a list or an array. (For an array, this may or may not be the index of the last member, depending on the array's origin.)

ascii

`ASCII char`

outputs the integer (between 0 and 255) that represents the input character in the ASCII code. Interprets control characters as representing backslashed punctuation, and returns the character code for the corresponding punctuation character without backslash. (Compare RAWASCII.)

rawascii

`RAWASCII char`

outputs the integer (between 0 and 255) that represents the input character in the ASCII code. Interprets control characters as representing themselves. To find out the ASCII code of an arbitrary keystroke, use `RAWASCII RC`.

char

`CHAR int`

outputs the character represented in the ASCII code by the input, which must be an integer between 0 and 255.

See [ASCII], page 17 .

member

`MEMBER thing1 thing2`

if `thing2` is a word or list and if MEMBERP with these inputs would output TRUE, outputs the portion of `thing2` from the first instance of `thing1` to the end. If MEMBERP would output FALSE, outputs the empty word or list according to the type of `thing2`. It is an error for `thing2` to be an array.

See [MEMBERP], page 16 .

lowercase

LOWERCASE word

outputs a copy of the input word, but with all uppercase letters changed to the corresponding lowercase letter.

uppercase

UPPERCASE word

outputs a copy of the input word, but with all lowercase letters changed to the corresponding uppercase letter.

standout

STANDOUT thing

outputs a word that, when printed, will appear like the input but displayed in standout mode (boldface, reverse video, or whatever your terminal does for standout). The word contains terminal-specific magic characters at the beginning and end; in between is the printed form (as if displayed using TYPE) of the input. The output is always a word, even if the input is of some other type, but it may include spaces and other formatting characters. Note: a word output by STANDOUT while Logo is running on one terminal will probably not have the desired effect if printed on another type of terminal.

On the Macintosh, the way that standout works is incompatible with the use of characters whose ASCII code is greater than 127. Therefore, you have a choice to make: The instruction

CANINVERSE 0

disables standout, but enables the display of ASCII codes above 127, and the instruction

CANINVERSE 1

restores the default situation in which standout is enabled and the extra graphic characters cannot be printed.

parse

PARSE word

outputs the list that would result if the input word were entered in response to a READLIST operation. That is, **PARSE READWORD** has the same value as READLIST for the same characters read.

See [READLIST], page 22 , [READWORD], page 22

runparse

RUNPARSE wordorlist

outputs the list that would result if the input word or list were entered as an instruction line; characters such as infix operators and parentheses are separate members of the output. Note that sublists of a runparsed list are not themselves runparsed.

3 Communication

3.1 Transmitters

Note: If there is a variable named *PRINTDEPTHLIMIT* with a nonnegative integer value, then complex list and array structures will be printed only to the allowed depth. That is, members of members of... of members will be allowed only so far. The members omitted because they are just past the depth limit are indicated by an ellipsis for each one, so a too-deep list of two members will print as [... ...].

If there is a variable named *PRINTWIDTHLIMIT* with a nonnegative integer value, then only the first so many members of any array or list will be printed. A single ellipsis replaces all missing data within the structure. The width limit also applies to the number of characters printed in a word, except that a *PRINTWIDTHLIMIT* between 0 and 9 will be treated as if it were 10 when applied to words. This limit applies not only to the top-level printed datum but to any substructures within it.

See [PRINTDEPTHLIMIT], page 92 , [PRINTWIDTHLIMIT], page 92

If there is a variable named *FULLPRINTP* whose value is TRUE, then words that were created using backslash or vertical bar (to include characters that would otherwise not be treated as part of a word) are printed with the backslashes or vertical bars shown, so that the printed result could be re-read by Logo to produce the same value. If *FULLPRINTP* is TRUE then the empty word (however it was created) prints as | |. (Otherwise it prints as nothing at all.)

See [FULLPRINTP], page 91 .

print

```
PRINT thing
PR thing
(PRINT thing1 thing2 ...)
(PR thing1 thing2 ...)
```

command. Prints the input or inputs to the current write stream (initially the terminal). All the inputs are printed on a single line, separated by spaces, ending with a newline. If an input is a list, square brackets are not printed around it, but brackets are printed around sublists. Braces are always printed around arrays.

type

```
TYPE thing
(TYPE thing1 thing2 ...)
```

command. Prints the input or inputs like PRINT, except that no newline character is printed at the end and multiple inputs are not separated by spaces. Note: printing to the terminal is ordinarily "line buffered"; that is, the characters you print using TYPE will not actually appear on the screen until either a newline character is printed (for example,

by PRINT or SHOW) or Logo tries to read from the keyboard (either at the request of your program or after an instruction prompt). This buffering makes the program much faster than it would be if each character appeared immediately, and in most cases the effect is not disconcerting. To accommodate programs that do a lot of positioned text display using TYPE, Logo will force printing whenever SETCURSOR is invoked. This solves most buffering problems. Still, on occasion you may find it necessary to force the buffered characters to be printed explicitly; this can be done using the WAIT command. WAIT 0 will force printing without actually waiting.

See [SETCURSOR], page 28 , [WAIT], page 73

show

```
SHOW thing
(SHOW thing1 thing2 ...)
```

command. Prints the input or inputs like PRINT, except that if an input is a list it is printed inside square brackets.

See [PRINT], page 21 .

3.2 Receivers

readlist

```
READLIST
RL
```

reads a line from the read stream (initially the terminal) and outputs that line as a list. The line is separated into members as though it were typed in square brackets in an instruction. If the read stream is a file, and the end of file is reached, READLIST outputs the empty word (not the empty list). READLIST processes backslash, vertical bar, and tilde characters in the read stream; the output list will not contain these characters but they will have had their usual effect. READLIST does not, however, treat semicolon as a comment character.

readword

```
READWORD
RW
```

reads a line from the read stream and outputs that line as a word. The output is a single word even if the line contains spaces, brackets, etc. If the read stream is a file, and the end of file is reached, READWORD outputs the empty list (not the empty word). READWORD processes backslash, vertical bar, and tilde characters in the read stream. In the case of a tilde used for line continuation, the output word DOES include the tilde and the newline characters, so that the user program can tell exactly what the user entered. Vertical bars in the line are also preserved in the output. Backslash characters are not preserved in the output, but the character following the backslash has 128 added to its representation.

Programs can use BACKSLASHEDP to check for this code. (Backslashedness is preserved only for certain characters.)

See [BACKSLASHEDP], page 16 .

readrawline

READRAWLINE

reads a line from the read stream and outputs that line as a word. The output is a single word even if the line contains spaces, brackets, etc. If the read stream is a file, and the end of file is reached, READRAWLINE outputs the empty list (not the empty word). READRAWLINE outputs the exact string of characters as they appear in the line, with no special meaning for backslash, vertical bar, tilde, or any other formatting characters.

See [READWORD], page 22 .

readchar

READCHAR

RC

reads a single character from the read stream and outputs that character as a word. If the read stream is a file, and the end of file is reached, READCHAR outputs the empty list (not the empty word). If the read stream is a terminal, echoing is turned off when READCHAR is invoked, and remains off until READLIST or READWORD is invoked or a Logo prompt is printed. Backslash, vertical bar, and tilde characters have no special meaning in this context.

See [READLIST], page 22 .

readchars

READCHARS num

RCS num

reads **num** characters from the read stream and outputs those characters as a word. If the read stream is a file, and the end of file is reached, READCHARS outputs the empty list (not the empty word). If the read stream is a terminal, echoing is turned off when READCHARS is invoked, and remains off until READLIST or READWORD is invoked or a Logo prompt is printed. Backslash, vertical bar, and tilde characters have no special meaning in this context.

See [READLIST], page 22 , [READWORD], page 22

shell

SHELL command

(SHELL command wordflag)

Under Unix, outputs the result of running **command** as a shell command. (The command is sent to `/bin/sh`, not `csh` or other alternatives.) If the command is a literal list in the instruction line, and if you want a backslash character sent to the shell, you must use `\\` to get the backslash through Logo's reader intact. The output is a list containing one member for each line generated by the shell command. Ordinarily each such line is represented by a list in the output, as though the line were read using `READLIST`. If a second input is given, regardless of the value of the input, each line is represented by a word in the output as though it were read with `READWORD`. Example:

```
to dayofweek
  output first first shell [date]
end
```

This is "first first" to extract the first word of the first (and only) line of the shell output.

Under DOS, `SHELL` is a command, not an operation; it sends its input to a DOS command processor but does not collect the result of the command.

The Macintosh, of course, is not programmable (unless you are running the Unix version of UCBLogo under OS X).

3.3 File Access

setprefix

```
SETPREFIX string
```

command. Sets a prefix that will be used as the implicit beginning of filenames in `OPENREAD`, `OPENWRITE`, `OPENAPPEND`, `OPENUPDATE`, `LOAD`, and `SAVE` commands. Logo will put the appropriate separator character (slash for Unix, backslash for DOS/Windows, colon for MacOS) between the prefix and the filename entered by the user. The input to `SETPREFIX` must be a word, unless it is the empty list, to indicate that there should be no prefix.

See [`OPENREAD`], page 24 , See [`OPENWRITE`], page 25 , See [`OPENAPPEND`], page 25 , See [`OPENUPDATE`], page 25 , See [`LOAD`], page 66 , See [`SAVE`], page 65 .

prefix

```
PREFIX
```

outputs the current file prefix, or `[]` if there is no prefix.

See [`SETPREFIX`], page 24 .

openread

```
OPENREAD filename
```

command. Opens the named file for reading. The read position is initially at the beginning of the file.

openwrite

`OPENWRITE filename`

command. Opens the named file for writing. If the file already existed, the old version is deleted and a new, empty file created.

openappend

`OPENAPPEND filename`

command. Opens the named file for writing. If the file already exists, the write position is initially set to the end of the old file, so that newly written data will be appended to it.

openupdate

`OPENUPDATE filename`

command. Opens the named file for reading and writing. The read and write position is initially set to the end of the old file, if any. Note: each open file has only one position, for both reading and writing. If a file opened for update is both `READER` and `WRITER` at the same time, then `SETREADPOS` will also affect `WRITEPOS` and vice versa. Also, if you alternate reading and writing the same file, you must `SETREADPOS` between a write and a read, and `SETWRITEPOS` between a read and a write.

See `[READER]`, page 27 , `[WRITER]`, page 27 , `[SETREADPOS]`, page 27 , `[SETWRITEPOS]`, page 27

close

`CLOSE filename`

command. Closes the named file.

allopen

`ALLOPEN`

outputs a list whose members are the names of all files currently open. This list does not include the dribble file, if any.

closeall

`CLOSEALL (library procedure)`

command. Closes all open files. Abbreviates `FOREACH ALLOPEN [CLOSE ?]`

See `[FOREACH]`, page 79 , `[CLOSE]`, page 25

erasefile

ERASEFILE filename
ERF filename

command. Erases (deletes, removes) the named file, which should not currently be open.

dribble

DRIBBLE filename

command. Creates a new file whose name is the input, like OPENWRITE, and begins recording in that file everything that is read from the keyboard or written to the terminal. That is, this writing is in addition to the writing to WRITER. The intent is to create a transcript of a Logo session, including things like prompt characters and interactions.

See [OPENWRITE], page 25 , [WRITER], page 27

nodribble

NODRIBBLE

command. Stops copying information into the dribble file, and closes the file.

setread

SETREAD filename

command. Makes the named file the read stream, used for READLIST, etc. The file must already be open with OPENREAD or OPENUPDATE. If the input is the empty list, then the read stream becomes the terminal, as usual. Changing the read stream does not close the file that was previously the read stream, so it is possible to alternate between files.

See [READLIST], page 22 , [OPENREAD], page 24 , [OPENUPDATE], page 25

setwrite

SETWRITE filename

command. Makes the named file the write stream, used for PRINT, etc. The file must already be open with OPENWRITE, OPENAPPEND, or OPENUPDATE. If the input is the empty list, then the write stream becomes the terminal, as usual. If the input is a list, then its first element must be a variable name, and its second and last element must be a positive integer; a buffer of that many characters will be allocated, and will become the writestream; when another SETWRITE is done, the contents of the buffer (as an unparsed word, which may contain newline characters) will become the value of the named variable. Changing the write stream does not close the file that was previously the write stream, so it is possible to alternate between files.

See [PRINT], page 21 , [OPENWRITE], page 25 ; [OPENAPPEND], page 25 ; [OPENUPDATE], page 25

reader

READER

outputs the name of the current read stream file, or the empty list if the read stream is the terminal.

writer

WRITER

outputs the name of the current write stream file, or the empty list if the write stream is the terminal.

setreadpos

SETREADPOS charpos

command. Sets the file pointer of the read stream file so that the next READLIST, etc., will begin reading at the **charpos**th character in the file, counting from 0. (That is, SETREADPOS 0 will start reading from the beginning of the file.) Meaningless if the read stream is the terminal.

See [READLIST], page 22 .

setwritepos

SETWRITEPOS charpos

command. Sets the file pointer of the write stream file so that the next PRINT, etc., will begin writing at the **charpos**th character in the file, counting from 0. (That is, SETWRITEPOS 0 will start writing from the beginning of the file.) Meaningless if the write stream is the terminal.

See [PRINT], page 21 .

readpos

READPOS

outputs the file position of the current read stream file.

writepos

WRITEPOS

outputs the file position of the current write stream file.

eofp

EOFP

EOF?

predicate, outputs TRUE if there are no more characters to be read in the read stream file, FALSE otherwise.

filep

FILEP filename
FILE? filename (library procedure)

predicate, outputs TRUE if a file of the specified name exists and can be read, FALSE otherwise.

3.4 Terminal Access

keyp

KEYP
KEY?

predicate, outputs TRUE if there are characters waiting to be read from the read stream. If the read stream is a file, this is equivalent to **NOT EOF?**. If the read stream is the terminal, then echoing is turned off and the terminal is set to CBREAK (character at a time instead of line at a time) mode. It remains in this mode until some line-mode reading is requested (e.g., READLIST). The Unix operating system forgets about any pending characters when it switches modes, so the first KEYP invocation will always output FALSE.

See [EOFP], page 27 , [READLIST], page 22

cleartext

CLEARTEXT
CT

command. Clears the text screen of the terminal.

setcursor

SETCURSOR vector

command. The input is a list of two numbers, the x and y coordinates of a screen position (origin in the upper left corner, positive direction is southeast). The screen cursor is moved to the requested position. This command also forces the immediate printing of any buffered characters.

cursor

CURSOR

outputs a list containing the current x and y coordinates of the screen cursor. Logo may get confused about the current cursor position if, e.g., you type in a long line that wraps around or your program prints escape codes that affect the terminal strangely.

setmargins

SETMARGINS *vector*

command. The input must be a list of two numbers, as for SETCURSOR. The effect is to clear the screen and then arrange for all further printing to be shifted down and to the right according to the indicated margins. Specifically, every time a newline character is printed (explicitly or implicitly) Logo will type *x*-margin spaces, and on every invocation of SETCURSOR the margins will be added to the input x and y coordinates. (CURSOR will report the cursor position relative to the margins, so that this shift will be invisible to Logo programs.) The purpose of this command is to accommodate the display of terminal screens in lecture halls with inadequate TV monitors that miss the top and left edges of the screen.

See [SETCURSOR], page 28 .

settextcolor

SETTEXTCOLOR *foreground background*
SETTC *foreground background*

Command (Windows and DOS extended only). The inputs are color numbers, as for turtle graphics. Future printing to the text window will use the specified colors for foreground (the characters printed) and background (the space under those characters). Using STANDOUT will revert to the default text window colors. In the DOS extended (ucblogo.exe) version, colors in textscreen mode are limited to numbers 0-7, and the coloring applies only to text printed by the program, not to the echoing of text typed by the user. Neither limitation applies to the text portion of splitscreen mode, which is actually drawn as graphics internally.

See [STANDOUT], page 18 .

4 Arithmetic

4.1 Numeric Operations

sum

```
SUM num1 num2
(SUM num1 num2 num3 ...)
num1 + num2
```

outputs the sum of its inputs.

difference

```
DIFFERENCE num1 num2
num1 - num2
```

outputs the difference of its inputs. Minus sign means infix difference in ambiguous contexts (when preceded by a complete expression), unless it is preceded by a space and followed by a nonspace. (See also MINUS.)

minus

```
MINUS num
- num
```

outputs the negative of its input. Minus sign means unary minus if it is immediately preceded by something requiring an input, or preceded by a space and followed by a nonspace. There is a difference in binding strength between the two forms:

MINUS 3 + 4	means	-(3+4)
- 3 + 4	means	(-3)+4

product

```
PRODUCT num1 num2
(PRODUCT num1 num2 num3 ...)
num1 * num2
```

outputs the product of its inputs.

quotient

```
QUOTIENT num1 num2
(QUOTIENT num)
num1 / num2
```

outputs the quotient of its inputs. The quotient of two integers is an integer if and only if the dividend is a multiple of the divisor. (In other words, `QUOTIENT 5 2` is 2.5, not 2, but

QUOTIENT 4 2 is 2, not 2.0 — it does the right thing.) With a single input, QUOTIENT outputs the reciprocal of the input.

remainder

REMAINDER num1 num2

outputs the remainder on dividing **num1** by **num2**; both must be integers and the result is an integer with the same sign as num1.

modulo

MODULO num1 num2

outputs the remainder on dividing **num1** by **num2**; both must be integers and the result is an integer with the same sign as num2.

int

INT num

outputs its input with fractional part removed, i.e., an integer with the same sign as the input, whose absolute value is the largest integer less than or equal to the absolute value of the input.

round

ROUND num

outputs the nearest integer to the input.

sqrt

SQRT num

outputs the square root of the input, which must be nonnegative.

power

POWER num1 num2

outputs **num1** to the **num2** power. If num1 is negative, then num2 must be an integer.

exp

EXP num

outputs e (2.718281828+) to the input power.

log10

`LOG10 num`

outputs the common logarithm of the input.

ln

`LN num`

outputs the natural logarithm of the input.

sin

`SIN degrees`

outputs the sine of its input, which is taken in degrees.

radsin

`RADSIN radians`

outputs the sine of its input, which is taken in radians.

cos

`COS degrees`

outputs the cosine of its input, which is taken in degrees.

radcos

`RADCOS radians`

outputs the cosine of its input, which is taken in radians.

arctan

`ARCTAN num`
`(ARCTAN x y)`

outputs the arctangent, in degrees, of its input. With two inputs, outputs the arctangent of y/x , if x is nonzero, or 90 or -90 depending on the sign of y , if x is zero.

radarctan

`RADARCTAN num`
`(RADARCTAN x y)`

outputs the arctangent, in radians, of its input. With two inputs, outputs the arctangent of y/x , if x is nonzero, or $\pi/2$ or $-\pi/2$ depending on the sign of y , if x is zero.

The expression `2*(RADARCTAN 0 1)` can be used to get the value of π .

iseq

ISEQ from to (library procedure)

outputs a list of the integers from FROM to TO, inclusive.

```
? show iseq 3 7
[3 4 5 6 7]
? show iseq 7 3
[7 6 5 4 3]
```

rseq

RSEQ from to count (library procedure)

outputs a list of COUNT equally spaced rational numbers between FROM and TO, inclusive.

```
? show rseq 3 5 9
[3 3.25 3.5 3.75 4 4.25 4.5 4.75 5]
? show rseq 3 5 5
[3 3.5 4 4.5 5]
```

4.2 Numeric Predicates

lessp

```
LESSP num1 num2
LESS? num1 num2
num1 < num2
```

outputs TRUE if its first input is strictly less than its second.

greaterp

```
GREATERP num1 num2
GREATER? num1 num2
num1 > num2
```

outputs TRUE if its first input is strictly greater than its second.

4.3 Random Numbers

random

RANDOM num

outputs a random nonnegative integer less than its input, which must be an integer.

rerandom

```
RERANDOM
(RERANDOM seed)
```

command. Makes the results of `RANDOM` reproducible. Ordinarily the sequence of random numbers is different each time Logo is used. If you need the same sequence of pseudo-random numbers repeatedly, e.g. to debug a program, say `RERANDOM` before the first invocation of `RANDOM`. If you need more than one repeatable sequence, you can give `RERANDOM` an integer input; each possible input selects a unique sequence of numbers.

4.4 Print Formatting**form**

```
FORM num width precision
```

outputs a word containing a printable representation of `num`, possibly preceded by spaces (and therefore not a number for purposes of performing arithmetic operations), with at least `width` characters, including exactly `precision` digits after the decimal point. (If `precision` is 0 then there will be no decimal point in the output.)

As a debugging feature, (`FORM num -1 format`) will print the floating point `num` according to the C `printf` `format`, to allow

```
to hex :num
  op form :num -1 "%08X %08X|
end
```

to allow finding out the exact result of floating point operations. The precise format needed may be machine-dependent.

4.5 Bitwise Operations**bitand**

```
BITAND num1 num2
(BITAND num1 num2 num3 ...)
```

outputs the bitwise AND of its inputs, which must be integers.

See [AND], page 37 .

bitor

```
BITOR num1 num2
(BITOR num1 num2 num3 ...)
```

outputs the bitwise OR of its inputs, which must be integers.

See [OR], page 37 .

bitxor

```
BITXOR num1 num2  
(BITXOR num1 num2 num3 ...)
```

outputs the bitwise EXCLUSIVE OR of its inputs, which must be integers.

See [OR], page 37 .

bitnot

```
BITNOT num
```

outputs the bitwise NOT of its input, which must be an integer.

See [NOT], page 37 .

ashift

```
ASHIFT num1 num2
```

outputs **num1** arithmetic-shifted to the left by **num2** bits. If **num2** is negative, the shift is to the right with sign extension. The inputs must be integers.

lshift

```
LSHIFT num1 num2
```

outputs **num1** logical-shifted to the left by **num2** bits. If **num2** is negative, the shift is to the right with zero fill. The inputs must be integers.

5 Logical Operations

and

```
AND tf1 tf2
(AND tf1 tf2 tf3 ...)
```

outputs TRUE if all inputs are TRUE, otherwise FALSE. All inputs must be TRUE or FALSE. (Comparison is case-insensitive regardless of the value of CASEIGNOREDP. That is, `true` or `True` or `TRUE` are all the same.) An input can be a list, in which case it is taken as an expression to run; that expression must produce a TRUE or FALSE value. List expressions are evaluated from left to right; as soon as a FALSE value is found, the remaining inputs are not examined. Example:

```
MAKE "RESULT AND [NOT (:X = 0)] [(1 / :X) > .5]
```

to avoid the division by zero if the first part is false.

See [CASEIGNOREDP], page 91 .

or

```
OR tf1 tf2
(OR tf1 tf2 tf3 ...)
```

outputs TRUE if any input is TRUE, otherwise FALSE. All inputs must be TRUE or FALSE. (Comparison is case-insensitive regardless of the value of CASEIGNOREDP. That is, `true` or `True` or `TRUE` are all the same.) An input can be a list, in which case it is taken as an expression to run; that expression must produce a TRUE or FALSE value. List expressions are evaluated from left to right; as soon as a TRUE value is found, the remaining inputs are not examined. Example:

```
IF OR :X=0 [some.long.computation] [...]
```

to avoid the long computation if the first condition is met.

See [CASEIGNOREDP], page 91 .

not

```
NOT tf
```

outputs TRUE if the input is FALSE, and vice versa. The input can be a list, in which case it is taken as an expression to run; that expression must produce a TRUE or FALSE value.

6 Graphics

Berkeley Logo provides traditional Logo turtle graphics with one turtle. Multiple turtles, dynamic turtles, and collision detection are not supported. This is the most hardware-dependent part of Logo; some features may exist on some machines but not others. Nevertheless, the goal has been to make Logo programs as portable as possible, rather than to take fullest advantage of the capabilities of each machine. In particular, Logo attempts to scale the screen so that turtle coordinates $[-100 -100]$ and $[100 100]$ fit on the graphics window, and so that the aspect ratio is 1:1, although some PC screens have nonstandard aspect ratios.

The center of the graphics window (which may or may not be the entire screen, depending on the machine used) is turtle location $[0 0]$. Positive X is to the right; positive Y is up. Headings (angles) are measured in degrees clockwise from the positive Y axis. (This differs from the common mathematical convention of measuring angles counterclockwise from the positive X axis.) The turtle is represented as an isosceles triangle; the actual turtle position is at the midpoint of the base (the short side).

Colors are, of course, hardware-dependent. However, Logo provides partial hardware independence by interpreting color numbers 0 through 7 uniformly on all computers:

0	black	1	blue	2	green	3	cyan
4	red	5	magenta	6	yellow	7	white

Where possible, Logo provides additional user-settable colors; how many are available depends on the hardware and operating system environment. If at least 16 colors are available, Logo tries to provide uniform initial settings for the colors 8-15:

8	brown	9	tan	10	forest	11	aqua
12	salmon	13	purple	14	orange	15	grey

Logo begins with a black background and white pen.

6.1 Turtle Motion

forward

```
FORWARD dist
FD dist
```

moves the turtle forward, in the direction that it's facing, by the specified distance (measured in turtle steps).

back

```
BACK dist
BK dist
```

moves the turtle backward, i.e., exactly opposite to the direction that it's facing, by the specified distance. (The heading of the turtle does not change.)

left

LEFT degrees
LT degrees

turns the turtle counterclockwise by the specified angle, measured in degrees (1/360 of a circle).

right

RIGHT degrees
RT degrees

turns the turtle clockwise by the specified angle, measured in degrees (1/360 of a circle).

setpos

SETPOS pos

moves the turtle to an absolute screen position. The input is a list of two numbers, the X and Y coordinates.

setxy

SETXY xcor ycor

moves the turtle to an absolute screen position. The two inputs are numbers, the X and Y coordinates.

setx

SETX xcor

moves the turtle horizontally from its old position to a new absolute horizontal coordinate. The input is the new X coordinate.

sety

SETY ycor

moves the turtle vertically from its old position to a new absolute vertical coordinate. The input is the new Y coordinate.

setheading

SETHEADING degrees
SETH degrees

turns the turtle to a new absolute heading. The input is a number, the heading in degrees clockwise from the positive Y axis.

home

HOME

moves the turtle to the center of the screen. Equivalent to `SETPOS [0 0] SETHEADING 0`.
See [SETPOS], page 40 , See [SETHEADING], page 40 .

arc

ARC angle radius

draws an arc of a circle, with the turtle at the center, with the specified radius, starting at the turtle's heading and extending clockwise through the specified angle. The turtle does not move.

6.2 Turtle Motion Queries

pos

POS

outputs the turtle's current position, as a list of two numbers, the X and Y coordinates.

xcor

XCOR (library procedure)

outputs a number, the turtle's X coordinate.

ycor

YCOR (library procedure)

outputs a number, the turtle's Y coordinate.

heading

HEADING

outputs a number, the turtle's heading in degrees.

towards

TOWARDS pos

outputs a number, the heading at which the turtle should be facing so that it would point from its current position to the position given as the input.

scrunch

SCRUNCH

outputs a list containing two numbers, the X and Y scrunch factors, as used by SETSCRUNCH. (But note that SETSCRUNCH takes two numbers as inputs, not one list of numbers.)

See [SETSCRUNCH], page 44 .

6.3 Turtle and Window Control

showturtle

SHOWTURTLE
ST

makes the turtle visible.

hideturtle

HIDETURTLE
HT

makes the turtle invisible. It's a good idea to do this while you're in the middle of a complicated drawing, because hiding the turtle speeds up the drawing substantially.

clean

CLEAN

erases all lines that the turtle has drawn on the graphics window. The turtle's state (position, heading, pen mode, etc.) is not changed.

clearscreen

CLEARSCREEN
CS

erases the graphics window and sends the turtle to its initial position and heading. Like HOME and CLEAN together.

See [HOME], page 41 .

wrap

WRAP

tells the turtle to enter wrap mode: From now on, if the turtle is asked to move past the boundary of the graphics window, it will "wrap around" and reappear at the opposite edge

of the window. The top edge wraps to the bottom edge, while the left edge wraps to the right edge. (So the window is topologically equivalent to a torus.) This is the turtle's initial mode. Compare WINDOW and FENCE.

See [FENCE], page 43 .

window

WINDOW

tells the turtle to enter window mode: From now on, if the turtle is asked to move past the boundary of the graphics window, it will move offscreen. The visible graphics window is considered as just part of an infinite graphics plane; the turtle can be anywhere on the plane. (If you lose the turtle, HOME will bring it back to the center of the window.) Compare WRAP and FENCE.

See [HOME], page 41 .

fence

FENCE

tells the turtle to enter fence mode: From now on, if the turtle is asked to move past the boundary of the graphics window, it will move as far as it can and then stop at the edge with an "out of bounds" error message. Compare WRAP and WINDOW.

See [WRAP], page 42 .

fill

FILL

fills in a region of the graphics window containing the turtle and bounded by lines that have been drawn earlier. This is not portable; it doesn't work for all machines, and may not work exactly the same way on different machines.

label

LABEL text

takes a word or list as input, and prints the input on the graphics window, starting at the turtle's position.

textscreen

TEXTSCREEN

TS

rearranges the size and position of windows to maximize the space available in the text window (the window used for interaction with Logo). The details differ among machines. Compare SPLITSCREEN and FULLSCREEN.

See [SPLITSCREEN], page 44 .

fullscreen

FULLSCREEN
FS

rearranges the size and position of windows to maximize the space available in the graphics window. The details differ among machines. Compare SPLITSCREEN and TEXTSCREEN.

In the DOS version, switching from fullscreen to splitscreen loses the part of the picture that's hidden by the text window. Also, since there must be a text window to allow printing (including the printing of the Logo prompt), Logo automatically switches from fullscreen to splitscreen whenever anything is printed. [This design decision follows from the scarcity of memory, so that the extra memory to remember an invisible part of a drawing seems too expensive.]

splitscreen

SPLITSCREEN
SS

rearranges the size and position of windows to allow some room for text interaction while also keeping most of the graphics window visible. The details differ among machines. Compare TEXTSCREEN and FULLSCREEN.

See [TEXTSCREEN], page 43 .

setscrunch

SETSCRUNCH *xscale* *yscale*

adjusts the aspect ratio and scaling of the graphics display. After this command is used, all further turtle motion will be adjusted by multiplying the horizontal and vertical extent of the motion by the two numbers given as inputs. For example, after the instruction **SETSCRUNCH 2 1** motion at a heading of 45 degrees will move twice as far horizontally as vertically. If your squares don't come out square, try this. (Alternatively, you can deliberately misadjust the aspect ratio to draw an ellipse.)

For Unix machines and Macintoshes, both scale factors are initially 1. For DOS machines, the scale factors are initially set according to what the hardware claims the aspect ratio is, but the hardware sometimes lies. The values set by SETSCRUNCH are remembered in a file (called SCRUNCH.DAT) and are automatically put into effect when a Logo session begins.

refresh

REFRESH

tells Logo to remember the turtle's motions so that they can be reconstructed in case the graphics window is overlayed. The effectiveness of this command may depend on the machine used.

norefresh

NOREFRESH

tells Logo not to remember the turtle's motions. This will make drawing faster, but prevents recovery if the window is overlayed.

6.4 Turtle and Window Queries

shownp

SHOWNP
SHOWN?

outputs TRUE if the turtle is shown (visible), FALSE if the turtle is hidden. See SHOW-TURTLE and HIDE-TURTLE.

See [SHOW-TURTLE], page 42 , [HIDE-TURTLE], page 42 .

screenmode

SCREENMODE

outputs the word TEXTSCREEN, SPLITSCREEN, or FULLSCREEN depending on the current screen mode.

turtlemode

TURTLEMODE

outputs the word WRAP, FENCE, or WINDOW depending on the current turtle mode.

6.5 Pen and Background Control

The turtle carries a pen that can draw pictures. At any time the pen can be UP (in which case moving the turtle does not change what's on the graphics screen) or DOWN (in which case the turtle leaves a trace). If the pen is down, it can operate in one of three modes: PAINT (so that it draws lines when the turtle moves), ERASE (so that it erases any lines that might have been drawn on or through that path earlier), or REVERSE (so that it inverts the status of each point along the turtle's path).

pendown

PENDOWN

PD

sets the pen's position to DOWN, without changing its mode.

penup

PENUP

PU

sets the pen's position to UP, without changing its mode.

penpaint

PENPAINT

PPT

sets the pen's position to DOWN and mode to PAINT.

penerase

PENERASE

PE

sets the pen's position to DOWN and mode to ERASE.

See [ERASE], page 60 .

penreverse

PENREVERSE

PX

sets the pen's position to DOWN and mode to REVERSE. (This may interact in hardware-dependent ways with use of color.)

See [REVERSE], page 10 .

setpencolor

SETPENCOLOR colornumber

SETPC colornumber

sets the pen color to the given number, which must be a nonnegative integer. Color 0 is always black; color 7 is always white. Other colors may or may not be consistent between machines.

setpalette

SETPALETTE colornumber rgblist

sets the actual color corresponding to a given number, if allowed by the hardware and operating system. Colornumber must be an integer greater than or equal to 8. (Logo tries

to keep the first 8 colors constant.) The second input is a list of three nonnegative integers less than 64K (65536) specifying the amount of red, green, and blue in the desired color. The actual color resolution on any screen is probably less than 64K, but Logo scales as needed.

setpensize

```
SETPENSIZE size
SETPENPATTERN pattern
```

set hardware-dependent pen characteristics. These commands are not guaranteed compatible between implementations on different machines.

setpenpattern

```
SETPENSIZE size
SETPENPATTERN pattern
```

set hardware-dependent pen characteristics. These commands are not guaranteed compatible between implementations on different machines.

setpen

```
SETPEN list (library procedure)
```

sets the pen's position, mode, and hardware-dependent characteristics according to the information in the input list, which should be taken from an earlier invocation of PEN.

See [PEN], page 48 .

setbackground

```
SETBACKGROUND color
SETBG color
```

set the screen background color.

6.6 Pen Queries

pendownp

```
PENDOWNP
PENDOWN?
```

outputs TRUE if the pen is down, FALSE if it's up.

penmode

```
PENMODE
```


outputs one of the words PAINT, ERASE, or REVERSE according to the current pen mode.

See [ERASE], page 60 , [REVERSE], page 10 .

pencolor

```
PENCOLOR
PC
```

outputs a color number, a nonnegative integer that is associated with a particular color by the hardware and operating system.

palette

```
PALETTE colornumber
```

outputs a list of three integers, each in the range 0-65535, representing the amount of red, green, and blue in the color associated with the given number.

pensize

```
PENSIZE
PENPATTERN
```

output hardware-specific pen information.

pen

```
PEN (library procedure)
```

outputs a list containing the pen's position, mode, and hardware-specific characteristics, for use by SETPEN.

See [SETPEN], page 47 .

background

```
BACKGROUND
BG
```

outputs the graphics background color.

6.7 saving and loading pictures

savepict

```
SAVEPICT filename
```

command. Writes a file with the specified name containing the state of the graphics window, including any nonstandard color palette settings, in Logo's internal format. This picture can be restored to the screen using `LOADPICT`. The format is not portable between platforms, nor is it readable by other programs. [EPSPICT], page 49 to export Logo graphics for other programs.

loadpict

`LOADPICT filename`

command. Reads the specified file, which must have been written by a `SAVEPICT` command, and restores the graphics window and color palette settings to the values stored in the file. Any drawing previously on the screen is cleared.

See [SAVEPICT], page 48 .

epspict

`EPSPICT filename`

command. Writes a file with the specified name, containing an Encapsulated Postscript (EPS) representation of the state of the graphics window. This file can be imported into other programs that understand EPS format. Restrictions: the drawing cannot use `ARC`, `FILL`, `PENERASE`, or `PENREVERSE`; any such instructions will be ignored in the translation to Postscript form.

See [ARC], page 41 , See [FILL], page 43 , See [PENERASE], page 46 , See [PENREVERSE], page 46 .

7 Workspace Management

7.1 Procedure Definition

to

```
TO procname :input1 :input2 ... (special form)
```

command. Prepares Logo to accept a procedure definition. The procedure will be named **procname** and there must not already be a procedure by that name. The inputs will be called **input1** etc. Any number of inputs are allowed, including none. Names of procedures and inputs are case-insensitive.

Unlike every other Logo procedure, TO takes as its inputs the actual words typed in the instruction line, as if they were all quoted, rather than the results of evaluating expressions to provide the inputs. (That's what "**special form**" means.)

This version of Logo allows variable numbers of inputs to a procedure. After the procedure name come four kinds of things, *in this order*:

1. 0 or more REQUIRED inputs :FOO :FROBOZZ
2. 0 or more OPTIONAL inputs [:BAZ 87] [:THING0 5+9]
3. 0 or 1 REST input [:GARPLY]
4. 0 or 1 DEFAULT number 5

Every procedure has a MINIMUM, DEFAULT, and MAXIMUM number of inputs. (The latter can be infinite.)

The MINIMUM number of inputs is the number of required inputs, which must come first. A required input is indicated by the

```
:inputname
```

notation.

After all the required inputs can be zero or more optional inputs, each of which is represented by the following notation:

```
[:inputname default.value.expression]
```

When the procedure is invoked, if actual inputs are not supplied for these optional inputs, the default value expressions are evaluated to set values for the corresponding input names. The inputs are processed from left to right, so a default value expression can be based on earlier inputs. Example:

```
to proc :inlist [:startvalue first :inlist]
```

If the procedure is invoked by saying

```
proc [a b c]
```

then the variable **inlist** will have the value [A B C] and the variable **startvalue** will have the value A. If the procedure is invoked by saying

```
(proc [a b c] "x)
```

then **inlist** will have the value [A B C] and **startvalue** will have the value X.

After all the required and optional input can come a single **rest** input, represented by the following notation:

```
[:inputname]
```

This is a rest input rather than an optional input because there is no default value expression. There can be at most one rest input. When the procedure is invoked, the value of this input will be a list containing all of the actual inputs provided that were not used for required or optional inputs. Example:

```
to proc :in1 [:in2 "foo] [:in3 "baz] [:in4]
```

If this procedure is invoked by saying

```
proc "x
```

then **in1** has the value X, **in2** has the value FOO, **in3** has the value BAZ, and **in4** has the value [] (the empty list). If it's invoked by saying

```
(proc "a "b "c "d "e)
```

then **in1** has the value A, **in2** has the value B, **in3** has the value C, and **in4** has the value [D E].

The **MAXIMUM** number of inputs for a procedure is infinite if a rest input is given; otherwise, it is the number of required inputs plus the number of optional inputs.

The **DEFAULT** number of inputs for a procedure, which is the number of inputs that it will accept if its invocation is not enclosed in parentheses, is ordinarily equal to the minimum number. If you want a different default number you can indicate that by putting the desired default number as the last thing on the **TO** line. example:

```
to proc :in1 [:in2 "foo] [:in3] 3
```

This procedure has a minimum of one input, a default of three inputs, and an infinite maximum.

Logo responds to the **TO** command by entering procedure definition mode. The prompt character changes from ? to > and whatever instructions you type become part of the definition until you type a line containing only the word **END**.

define

```
DEFINE procname text
```

command. Defines a procedure with name **procname** and text **text**. If there is already a procedure with the same name, the new definition replaces the old one. The text input must be a list whose members are lists. The first member is a list of inputs; it looks like a **TO** line but without the word **TO**, without the procedure name, and without the colons before input names. In other words, the members of this first sublist are words for the names of

required inputs and lists for the names of optional or rest inputs. The remaining sublists of the text input make up the body of the procedure, with one sublist for each instruction line of the body. (There is no END line in the text input.) It is an error to redefine a primitive procedure unless the variable *REDEFP* has the value TRUE.

See [REDEFP], page 92 .

text

TEXT *procname*

outputs the text of the procedure named *procname* in the form expected by DEFINE: a list of lists, the first of which describes the inputs to the procedure and the rest of which are the lines of its body. The text does not reflect formatting information used when the procedure was defined, such as continuation lines and extra spaces.

fulltext

FULLTEXT *procname*

outputs a representation of the procedure *procname* in which formatting information is preserved. If the procedure was defined with TO, EDIT, or LOAD, then the output is a list of words. Each word represents one entire line of the definition in the form output by READWORD, including extra spaces and continuation lines. The last member of the output represents the END line. If the procedure was defined with DEFINE, then the output is a list of lists. If these lists are printed, one per line, the result will look like a definition using TO. Note: the output from FULLTEXT is not suitable for use as input to DEFINE!

See [TO], page 51 , [EDIT], page 64 , [LOAD], page 66 , [DEFINE], page 52 .

copydef

COPYDEF *newname oldname*

command. Makes *newname* a procedure identical to *oldname*. The latter may be a primitive. If *newname* was already defined, its previous definition is lost. If *newname* was already a primitive, the redefinition is not permitted unless the variable *REDEFP* has the value TRUE. Definitions created by COPYDEF are not saved by SAVE; primitives are never saved, and user-defined procedures created by COPYDEF are buried. (You are likely to be confused if you PO or POT a procedure defined with COPYDEF because its title line will contain the old name. This is why it's buried.)

Note: dialects of Logo differ as to the order of inputs to COPYDEF. This dialect uses "MAKE order," not "NAME order."

See [REDEFP], page 92 , [SAVE], page 65 , [PO], page 58 , [POT], page 60 .

7.2 Variable Definition

make

MAKE varname value

command. Assigns the value **value** to the variable named **varname**, which must be a word. Variable names are case-insensitive. If a variable with the same name already exists, the value of that variable is changed. If not, a new global variable is created.

name

NAME value varname (library procedure)

command. Same as **MAKE** but with the inputs in reverse order.

local

LOCAL varname
LOCAL varnamelist
 (**LOCAL** varname1 varname2 ...)

command. Accepts as inputs one or more words, or a list of words. A variable is created for each of these words, with that word as its name. The variables are local to the currently running procedure. Logo variables follow dynamic scope rules; a variable that is local to a procedure is available to any subprocedure invoked by that procedure. The variables created by **LOCAL** have no initial value; they must be assigned a value (e.g., with **MAKE**) before the procedure attempts to read their value.

See [MAKE], page 54 .

localmake

LOCALMAKE varname value (library procedure)

command. Makes the named variable local, like **LOCAL**, and assigns it the given value, like **MAKE**.

See [LOCAL], page 54 , See [MAKE], page 54 .

thing

THING varname
 :quoted.varname

outputs the value of the variable whose name is the input. If there is more than one such variable, the innermost local variable of that name is chosen. The colon notation is an abbreviation not for **THING** but for the combination

thing "

so that **:FOO** means **THING "FOO**.

global

```
GLOBAL varname
GLOBAL varnamelist
(GLOBAL varname1 varname2 ...)
```

command. Accepts as inputs one or more words, or a list of words. A global variable is created for each of these words, with that word as its name. The only reason this is necessary is that you might want to use the "setter" notation SETXYZ for a variable XYZ that does not already have a value; GLOBAL "XYZ makes that legal. Note: If there is currently a local variable of the same name, this command does **not** make Logo use the global value instead of the local one.

7.3 Property Lists

Note: Names of property lists are always case-insensitive. Names of individual properties are case-sensitive or case-insensitive depending on the value of *CASEIGNOREDP*, which is TRUE by default.

See [CASEIGNOREDP], page 91 .

In principle, every possible name is the name of a property list, which is initially empty. So Logo never gives a "no such property list" error, as it would for undefined procedure or variable names. But the primitive procedures that deal with "all" property lists (CONTENTS, PLISTS, etc.) list only nonempty ones. To "erase" a property list [ERASE], page 60 means to make it empty, removing all properties from it.

pprop

```
PPROP plistname propname value
```

command. Adds a property to the **plistname** property list with name **propname** and value **value**.

gprop

```
GPROP plistname propname
```

outputs the value of the **propname** property in the **plistname** property list, or the empty list if there is no such property.

remprop

```
REMPROP plistname propname
```

command. Removes the property named **propname** from the property list named **plistname**.

plist

```
PLIST plistname
```


outputs a list whose odd-numbered members are the names, and whose even-numbered members are the values, of the properties in the property list named `plistname`. The output is a copy of the actual property list; changing properties later will not magically change a list output earlier by `PLIST`.

7.4 Workspace Predicates

procedurep

```
PROCEDUREP name  
PROCEDURE? name
```

outputs TRUE if the input is the name of a procedure.

primitivep

```
PRIMITIVEP name  
PRIMITIVE? name
```

outputs TRUE if the input is the name of a primitive procedure (one built into Logo). Note that some of the procedures described in this document are library procedures, not primitives.

definedp

```
DEFINEDP name  
DEFINED? name
```

outputs TRUE if the input is the name of a user-defined procedure, including a library procedure. (However, Logo does not know about a library procedure until that procedure has been invoked.)

namep

```
NAMEP name  
NAME? name
```

outputs TRUE if the input is the name of a variable.

plistp

```
PLISTP name  
PLIST? name
```

outputs TRUE if the input is the name of a *nonempty* property list. (In principle every word is the name of a property list; if you haven't put any properties in it, `PLIST` of that name outputs an empty list, rather than giving an error message.)

7.5 Workspace Queries

contents

CONTENTS

outputs a "contents list," i.e., a list of three lists containing names of defined procedures, variables, and property lists respectively. This list includes all unburied named items in the workspace.

buried

BURIED

outputs a contents list including all buried named items in the workspace.

traced

TRACED

outputs a contents list including all traced named items in the workspace.

stepped

STEPPED

outputs a contents list including all stepped named items in the workspace.

procedures

PROCEDURES

outputs a list of the names of all unburied user-defined procedures in the workspace. Note that this is a list of names, not a contents list. (However, procedures that require a contents list as input will accept this list.)

names

NAMES

outputs a contents list consisting of an empty list (indicating no procedure names) followed by a list of all unburied variable names in the workspace.

plists

PLISTS

outputs a contents list consisting of two empty lists (indicating no procedures or variables) followed by a list of all unburied nonempty property lists in the workspace.

namelist

```
NAMELIST varname (library procedure)
NAMELIST varnamelist
```

outputs a contents list consisting of an empty list followed by a list of the name or names given as input. This is useful in conjunction with workspace control procedures that require a contents list as input.

plist

```
PLLIST plname (library procedure)
PLLIST plnamelist
```

outputs a contents list consisting of two empty lists followed by a list of the name or names given as input. This is useful in conjunction with workspace control procedures that require a contents list as input.

Note: All procedures whose input is indicated as **contentslist** will accept a single word (taken as a procedure name), a list of words (taken as names of procedures), or a list of three lists as described under the CONTENTS command above.

See [CONTENTS], page 57 .

arity

```
ARITY procedurename
```

outputs a list of three numbers: the minimum, default, and maximum number of inputs for the procedure whose name is the input. It is an error if there is no such procedure. A maximum of -1 means that the number of inputs is unlimited.

nodes

```
NODES
```

outputs a list of two numbers. The first represents the number of nodes of memory currently in use. The second shows the maximum number of nodes that have been in use at any time since the last invocation of NODES. (A node is a small block of computer memory as used by Logo. Each number uses one node. Each non-numeric word uses one node, plus some non-node memory for the characters in the word. Each array takes one node, plus some non-node memory, as well as the memory required by its elements. Each list requires one node per element, as well as the memory within the elements.) If you want to track the memory use of an algorithm, it is best if you invoke GC at the beginning of each iteration, since otherwise the maximum will include storage that is unused but not yet collected.

7.6 Workspace Inspection**po**

P0 contentslist

command. Prints to the write stream the definitions of all procedures, variables, and property lists named in the input contents list.

poall**POALL (library procedure)**

command. Prints all unburied definitions in the workspace. Abbreviates **P0 CONTENTS**.

See [CONTENTS], page 57 .

pops**POPS (library procedure)**

command. Prints the definitions of all unburied procedures in the workspace. Abbreviates **P0 PROCEDURES**.

See [PO], page 58 , [PROCEDURES], page 57 .

pons**PONS (library procedure)**

command. Prints the definitions of all unburied variables in the workspace. Abbreviates **P0 NAMES**.

See [PO], page 58 , [NAMES], page 57 .

popls**POPLS (library procedure)**

command. Prints the contents of all unburied nonempty property lists in the workspace. Abbreviates **P0 PLISTS**.

See [PO], page 58 , [PLISTS], page 57 .

pon**PON varname (library procedure)****PON varnamelist**

command. Prints the definitions of the named variable(s). Abbreviates **P0 NAMELIST varname(list)**.

See [PO], page 58 , [NAMELIST], page 58 .

popl

POPL *pname* (library procedure)
 POPL *plnamelist*

command. Prints the definitions of the named property list(s).
 Abbreviates PO PLLIST *pname(list)*.

See [PO], page 58 , [PLLIST], page 58 .

pot

POT *contentslist*

command. Prints the title lines of the named procedures and the definitions of the named variables and property lists. For property lists, the entire list is shown on one line instead of as a series of PPROP instructions as in PO.

See [PPROP], page 55 , [PO], page 58 .

pots

POTS (library procedure)

command. Prints the title lines of all unburied procedures in the workspace. Abbreviates POT PROCEDURES.

See [PROCEDURES], page 57 .

7.7 Workspace Control

erase

ERASE *contentslist*
 ER *contentslist*

command. Erases from the workspace the procedures, variables, and property lists named in the input. Primitive procedures may not be erased unless the variable *REDEFP* has the value TRUE.

See [REDEFP], page 92 .

erall

ERALL

command. Erases all unburied procedures, variables, and property lists from the workspace. Abbreviates ERASE CONTENTS.

See [CONTENTS], page 57 .

erps

ERPS

command. Erases all unburied procedures from the workspace.
Abbreviates **ERASE PROCEDURES**.

See [ERASE], page 60 , [PROCEDURES], page 57 .

erns**ERNS**

command. Erases all unburied variables from the workspace. Abbreviates **ERASE NAMES**.

See [ERASE], page 60 , [NAMES], page 57 .

erpls**ERPLS**

command. Erases all unburied property lists from the workspace.
Abbreviates **ERASE PLISTS**.

See [ERASE], page 60 , [PLISTS], page 57 .

ern

ERN varname (library procedure)
ERN varnamelist

command. Erases from the workspace the variable(s) named in the input. Abbreviates **ERASE NAMELIST varname(list)**.

See [ERASE], page 60 , [NAMELIST], page 58 .

erpl

ERPL pname (library procedure)
ERPL plnamelist

command. Erases from the workspace the property list(s) named in the input. Abbreviates **ERASE PLLIST pname(list)**.

See [ERASE], page 60 , [PLLIST], page 58 .

bury**BURY contentslist**

command. Buries the procedures, variables, and property lists named in the input. A buried item is not included in the lists output by **CONTENTS**, **PROCEDURES**, **VARIABLES**, and **PLISTS**, but is included in the list output by **BURIED**. By implication, buried things are not printed by **POALL** or saved by **SAVE**.

See [CONTENTS], page 57 , [PROCEDURES], page 57 , [PONS], page 59 , [PLISTS], page 57 , [POALL], page 59 , [SAVE], page 65 .

buryall

BURYALL (library procedure)

command. Abbreviates **BURY CONTENTS**.

See [CONTENTS], page 57 .

buryname

BURYNAMENAME varname (library procedure)
BURYNAMENAME varnamelist

command. Abbreviates **BURY NAMELIST varname(list)**.

See [BURY], page 61 , [NAMELIST], page 58 .

unbury

UNBURY contentslist

command. Unburies the procedures, variables, and property lists named in the input. That is, the named items will be returned to view in CONTENTS, etc.

See [CONTENTS], page 57 .

unburyall

UNBURYALL (library procedure)

command. Abbreviates **UNBURY BURIED**.

See [BURIED], page 57 .

unburyname

UNBURYNAME varname (library procedure)
UNBURYNAME varnamelist

command. Abbreviates **UNBURY NAMELIST varname(list)**.

See [UNBURY], page 62 , [NAMELIST], page 58 .

buriedp

BURIEDP contentslist
BURIED? contentslist

outputs TRUE if the first procedure, variable, or property list named in the contents list is buried, FALSE if not. Only the first thing in the list is tested; the most common use will be with a word as input, naming a procedure, but a contents list is allowed so that you can `BURIEDP [[] [VARIABLE]]` or `BURIEDP [[] [] [PROPLIST]]`.

trace

`TRACE contentslist`

command. Marks the named items for tracing. A message is printed whenever a traced procedure is invoked, giving the actual input values, and whenever a traced procedure STOPS or OUTPUTs. A message is printed whenever a new value is assigned to a traced variable using MAKE. A message is printed whenever a new property is given to a traced property list using PPROP.

See [STOP], page 71 , [OUTPUT], page 71 , [MAKE], page 54 , [PPROP], page 55 .

untrace

`UNTRACE contentslist`

command. Turns off tracing for the named items.

tracedp

`TRACEDP contentslist`

`TRACED? contentslist`

outputs TRUE if the first procedure, variable, or property list named in the contents list is traced, FALSE if not. Only the first thing in the list is tested; the most common use will be with a word as input, naming a procedure, but a contents list is allowed so that you can `TRACEDP [[] [VARIABLE]]` or `TRACEDP [[] [] [PROPLIST]]`.

step

`STEP contentslist`

command. Marks the named items for stepping. Whenever a stepped procedure is invoked, each instruction line in the procedure body is printed before being executed, and Logo waits for the user to type a newline at the terminal. A message is printed whenever a stepped variable name is 'shadowed' because a local variable of the same name is created either as a procedure input or by the LOCAL command.

See [LOCAL], page 54 .

unstep

`UNSTEP contentslist`

command. Turns off stepping for the named items.

steppedp

```
STEPPEDP contentslist
STEPPED? contentslist
```

outputs TRUE if the first procedure, variable, or property list named in the contents list is stepped, FALSE if not. Only the first thing in the list is tested; the most common use will be with a word as input, naming a procedure, but a contents list is allowed so that you can STEPPEDP [[] [VARIABLE]] or STEPPEDP [[] [] [PROPLIST]].

edit

```
EDIT contentslist
ED contentslist
(EDIT)
(ED)
```

command. If invoked with an input, EDIT writes the definitions of the named items into a temporary file and edits that file, using your favorite editor as determined by the *EDITOR* environment variable. If you don't have an *EDITOR* variable, edits the definitions using jove. If invoked without an input, EDIT edits the same file left over from a previous EDIT or EDITFILE instruction. When you leave the editor, Logo reads the revised definitions and modifies the workspace accordingly. It is not an error if the input includes names for which there is no previous definition.

If there is a variable *LOADNOISILY* whose value is TRUE, then, after leaving the editor, TO commands in the temporary file print "PROCNAME defined" (where PROCNAME is the name of the procedure being defined); if *LOADNOISILY* is FALSE or undefined, TO commands in the file are carried out silently.

If there is an environment variable called *TEMP*, then Logo uses its value as the directory in which to write the temporary file used for editing.

Exceptionally, the EDIT command can be used without its default input and without parentheses provided that nothing follows it on the instruction line.

See [LOADNOISILY], page 91 , See [EDITFILE], page 64 .

editfile

```
EDITFILE filename
```

command. Starts the Logo editor, like EDIT, but instead of editing a temporary file it edits the file specified by the input. When you leave the editor, Logo reads the revised file, as for EDIT. EDITFILE also remembers the filename, so that a subsequent EDIT command with no input will re-edit the same file.

EDITFILE is intended as an alternative to LOAD and SAVE. You can maintain a workspace file yourself, controlling the order in which definitions appear, maintaining comments in the file, and so on.

edall

EDALL (library procedure)

command. Abbreviates EDIT CONTENTS.

See [CONTENTS], page 57 .

edps

EDPS (library procedure)

command. Abbreviates EDIT PROCEDURES.

See [EDIT], page 64 , [PROCEDURES], page 57 .

edns

EDNS (library procedure)

command. Abbreviates EDIT NAMES.

See [EDIT], page 64 , [NAMES], page 57 .

edpls

EDPLS (library procedure)

command. Abbreviates EDIT PLISTS.

See [EDIT], page 64 , [PLISTS], page 57 .

edn

EDN varname (library procedure)

EDN varnamelist

command. Abbreviates EDIT NAMELIST varname(list).

See [EDIT], page 64 , [NAMELIST], page 58 .

edpl

EDPL pname (library procedure)

EDPL plnamelist

command. Abbreviates EDIT PLLIST pname(list).

See [EDIT], page 64 , [PLLIST], page 58 .

save

SAVE filename

command. Saves the definitions of all unburied procedures, variables, and nonempty property lists in the named file. Equivalent to

```
to save :filename
  local "oldwriter
  make "oldwriter writer
  openwrite :filename
  setwrite :filename
  poall
  setwrite :oldwriter
  close :filename
end
```

savel

SAVEL contentslist filename (library procedure)

command. Saves the definitions of the procedures, variables, and property lists specified by **contentslist** to the file named **filename**.

load

LOAD filename

command. Reads instructions from the named file and executes them. The file can include procedure definitions with **TO**, and these are accepted even if a procedure by the same name already exists. If the file assigns a list value to a variable named *STARTUP*, then that list is run as an instructionlist after the file is loaded. If there is a variable *LOADNOISILY* whose value is **TRUE**, then **TO** commands in the file print "PROCNAME defined" (where PROCNAME is the name of the procedure being defined); if *LOADNOISILY* is **FALSE** or undefined, **TO** commands in the file are carried out silently.

See [STARTUP], page 92 , See [LOADNOISILY], page 91 .

help

HELP name
(HELP)

command. Prints information from the reference manual about the primitive procedure named by the input. With no input, lists all the primitives about which help is available. If there is an environment variable *LOGOHELP*, then its value is taken as the directory in which to look for help files, instead of the default help directory.

If **HELP** is called with the name of a defined procedure for which there is no help file, it will print the title line of the procedure followed by lines from the procedure body that start with semicolon, stopping when a non-semicolon line is seen.

Exceptionally, the **HELP** command can be used without its default input and without parentheses provided that nothing follows it on the instruction line.

seteditor

SETEDITOR *path*

command. Tells Logo to use the specified program as its editor instead of the default editor. The format of a path depends on your operating system.

setlibloc

SETLIBLOC *path*

command. Tells Logo to use the specified directory as its library instead of the default. (Note that many Logo "primitive" procedures are actually found in the library, so they may become unavailable if your new library does not include them!) The format of a path depends on your operating system.

sethelploc

SETHELPLOC *path*

command. Tells Logo to look in the specified directory for the information provided by the **HELP** command, instead of the default directory. The format of a path depends on your operating system.

settemploc

SETTEMPLOC *path*

command. Tells Logo to write editor temporary files in the specified directory rather than in the default directory. You must have write permission for this directory. The format of a path depends on your operating system.

gc

GC
(GC anything)

command. Runs the garbage collector, reclaiming unused nodes. Logo does this when necessary anyway, but you may want to use this command to control exactly when Logo does it. In particular, the numbers output by the **NODES** operation will not be very meaningful unless garbage has been collected. Another reason to use **GC** is that a garbage collection takes a noticeable fraction of a second, and you may want to schedule collections for times before or after some time-critical animation. If invoked with an argument (of any value), **GC** runs a full garbage collection, including **GCTWA** (Garbage Collect Truly Worthless Atoms, which means that it removes from Logo's memory words that used to be procedure or variable names but aren't any more); without an argument, **GC** does a generational garbage collection, which means that only recently created nodes are examined. (The latter is usually good enough.)

.setsegmentsize**.SETSEGMENTSIZ** *num*

command. Sets the number of nodes that Logo allocates from the operating system at once to *num*, which must be a positive integer. The name is dotted because bad things will happen if you use a number that's too small or too large for your computer. The initial value is 16,000 for most systems, but is smaller for 68000-based Macs. Making it larger will speed up computations (by reducing the number of garbage collections) at the cost of allocating more memory than necessary.

8 Control Structures

8.1 Control

Note: in the following descriptions, an **instructionlist** can be a list or a word. In the latter case, the word is parsed into list form before it is run. Thus, **RUN READWORD** or **RUN READLIST** will work. The former is slightly preferable because it allows for a continued line (with ~) that includes a comment (with ;) on the first line.

A **tf** input must be the word **TRUE**, the word **FALSE**, or a list. If it's a list, then it must be a Logo expression, which will be evaluated to produce a value that must be **TRUE** or **FALSE**. The comparisons with **TRUE** and **FALSE** are always case-insensitive.

run

RUN instructionlist

command or operation. Runs the Logo instructions in the input list; outputs if the list contains an expression that outputs.

See [READWORD], page 22 , [READLIST], page 22 .

runresult

RUNRESULT instructionlist

runs the instructions in the input; outputs an empty list if those instructions produce no output, or a list whose only member is the output from running the input instructionlist. Useful for inventing command-or-operation control structures:

```
local "result
make "result runresult [something]
if empty? :result [stop]
output first :result
```

repeat

REPEAT num instructionlist

command. Runs the **instructionlist** repeatedly, **num** times.

forever

FOREVER instructionlist

command. Runs the "instructionlist" repeatedly, until something inside the instructionlist (such as **STOP** or **THROW**) makes it stop.

See [STOP], page 71 , See [THROW], page 71 .

repcount

REPCOUNT

outputs the repetition count of the innermost current REPEAT or FOREVER, starting from 1. If no REPEAT or FOREVER is active, outputs -1.

if

IF tf instructionlist
(IF tf instructionlist1 instructionlist2)

command. If the first input has the value TRUE, then IF runs the second input. If the first input has the value FALSE, then IF does nothing. (If given a third input, IF acts like IFELSE, as described below.) It is an error if the first input is not either TRUE or FALSE.

For compatibility with earlier versions of Logo, if an IF instruction is not enclosed in parentheses, but the first thing on the instruction line after the second input expression is a literal list (i.e., a list in square brackets), the IF is treated as if it were IFELSE, but a warning message is given. If this aberrant IF appears in a procedure body, the warning is given only the first time the procedure is invoked in each Logo session.

ifelse

IFELSE tf instructionlist1 instructionlist2

command or operation. If the first input has the value TRUE, then IFELSE runs the second input. If the first input has the value FALSE, then IFELSE runs the third input. IFELSE outputs a value if the instructionlist contains an expression that outputs a value.

test

TEST tf

command. Remembers its input, which must be TRUE or FALSE, for use by later IFTRUE or IFFALSE instructions. The effect of TEST is local to the procedure in which it is used; any corresponding IFTRUE or IFFALSE must be in the same procedure or a subprocedure.

See [IFFALSE], page 70 .

iftrue

IFTRUE instructionlist
IFT instructionlist

command. Runs its input if the most recent TEST instruction had a TRUE input. The TEST must have been in the same procedure or a superprocedure.

iffalse

IFFALSE instructionlist

IFF instructionlist

command. Runs its input if the most recent TEST instruction had a FALSE input. The TEST must have been in the same procedure or a superprocedure.

See [TEST], page 70 .

stop**STOP**

command. Ends the running of the procedure in which it appears. Control is returned to the context in which that procedure was invoked. The stopped procedure does not output a value.

output
OUTPUT value
OP value

command. Ends the running of the procedure in which it appears. That procedure outputs the value **value** to the context in which it was invoked. Don't be confused: OUTPUT itself is a command, but the procedure that invokes OUTPUT is an operation.

catch**CATCH tag instructionlist**

command or operation. Runs its second input. Outputs if that instructionlist outputs. If, while running the instructionlist, a THROW instruction is executed with a tag equal to the first input (case-insensitive comparison), then the running of the instructionlist is terminated immediately. In this case the CATCH outputs if a value input is given to THROW. The **tag** must be a word.

If the tag is the word ERROR, then any error condition that arises during the running of the instructionlist has the effect of THROW "ERROR instead of printing an error message and returning to toplevel. The CATCH does not output if an error is caught. Also, during the running of the instructionlist, the variable *ERRACT* is temporarily unbound. (If there is an error while *ERRACT* has a value, that value is taken as an instructionlist to be run after printing the error message. Typically the value of *ERRACT*, if any, is the list [PAUSE].)

See [ERROR], page 72 , [ERRACT], page 91 , [PAUSE], page 72 .

throw
THROW tag
(THROW tag value)

command. Must be used within the scope of a CATCH with an equal tag. Ends the running of the instructionlist of the CATCH. If THROW is used with only one input, the

corresponding CATCH does not output a value. If THROW is used with two inputs, the second provides an output for the CATCH.

THROW "TOPLEVEL can be used to terminate all running procedures and interactive pauses, and return to the toplevel instruction prompt. Typing the system interrupt character (normally control-C for Unix, control-Q for DOS, or command-period for Mac) has the same effect.

THROW "ERROR can be used to generate an error condition. If the error is not caught, it prints a message (THROW "ERROR) with the usual indication of where the error (in this case the THROW) occurred. If a second input is used along with a tag of ERROR, that second input is used as the text of the error message instead of the standard message. Also, in this case, the location indicated for the error will be, not the location of the THROW, but the location where the procedure containing the THROW was invoked. This allows user-defined procedures to generate error messages as if they were primitives. Note: in this case the corresponding CATCH "ERROR, if any, does not output, since the second input to THROW is not considered a return value.

THROW "SYSTEM immediately leaves Logo, returning to the operating system, without printing the usual parting message and without deleting any editor temporary file written by EDIT.

See [EDIT], page 64 .

error

ERROR

outputs a list describing the error just caught, if any. If there was not an error caught since the last use of ERROR, the empty list will be output. The error list contains four members: an integer code corresponding to the type of error, the text of the error message, the name of the procedure in which the error occurred, and the instruction line on which the error occurred.

pause

PAUSE

command or operation. Enters an interactive pause. The user is prompted for instructions, as at toplevel, but with a prompt that includes the name of the procedure in which PAUSE was invoked. Local variables of that procedure are available during the pause. PAUSE outputs if the pause is ended by a CONTINUE with an input.

If the variable *ERRACT* exists, and an error condition occurs, the contents of that variable are run as an instructionlist. Typically *ERRACT* is given the value [PAUSE] so that an interactive pause will be entered on the event of an error. This allows the user to check values of local variables at the time of the error.

Typing the system quit character (normally control-N for Unix, control-W for DOS, or command-comma for Mac) will also enter a pause.

See [ERRACT], page 91 .

continue

```
CONTINUE value
CO value
(CONTINUE)
(CO)
```

command. Ends the current interactive pause, returning to the context of the PAUSE invocation that began it. If CONTINUE is given an input, that value is used as the output from the PAUSE. If not, the PAUSE does not output.

Exceptionally, the CONTINUE command can be used without its default input and without parentheses provided that nothing follows it on the instruction line.

wait

```
WAIT time
```

command. Delays further execution for **time** 60ths of a second. Also causes any buffered characters destined for the terminal to be printed immediately. **WAIT 0** can be used to achieve this buffer flushing without actually waiting.

bye

```
BYE
```

command. Exits from Logo; returns to the operating system.

.maybeoutput

```
.MAYBEOUTPUT value (special form)
```

works like OUTPUT except that the expression that provides the input value might not, in fact, output a value, in which case the effect is like STOP. This is intended for use in control structure definitions, for cases in which you don't know whether or not some expression produces a value. Example:

```
to invoke :function [:inputs] 2
  .maybeoutput apply :function :inputs
end

? (invoke "print "a "b "c)
a b c
? print (invoke "word "a "b "c)
abc
```

This is an alternative to RUNRESULT. It's fast and easy to use, at the cost of being an exception to Logo's evaluation rules. (Ordinarily, it should be an error if the expression that's supposed to provide an input to something doesn't have a value.)

See [OUTPUT], page 71 , [STOP], page 71 , [RUNRESULT], page 69 .

goto

GOTO word

command. Looks for a TAG command with the same input in the same procedure, and continues running the procedure from the location of that TAG. It is meaningless to use GOTO outside of a procedure.

tag

TAG quoted.word

command. Does nothing. The input must be a literal word following a quotation mark ("), not the result of a computation. Tags are used by the GOTO command.

ignore

IGNORE value (library procedure)

command. Does nothing. Used when an expression is evaluated for a side effect and its actual value is unimportant.

‘

‘ list (library procedure)

outputs a list equal to its input but with certain substitutions. If a member of the input list is the word ‘,’ (comma) then the following member should be an instructionlist that produces an output when run. That output value replaces the comma and the instructionlist. If a member of the input list is the word ‘,@’ (comma atsign) then the following member should be an instructionlist that outputs a list when run. The members of that list replace the ‘,@’ and the instructionlist. Example:

```
show ‘[foo baz ,[bf [a b c]] garply ,@[bf [a b c]]]
```

will print

```
[foo baz [b c] garply b c]
```

for

FOR forcontrol instructionlist (library procedure)

command. The first input must be a list containing three or four members: (1) a word, which will be used as the name of a local variable; (2) a word or list that will be evaluated as by RUN to determine a number, the starting value of the variable; (3) a word or list that will be evaluated to determine a number, the limit value of the variable; (4) an optional word or list that will be evaluated to determine the step size. If the fourth member is

missing, the step size will be 1 or -1 depending on whether the limit value is greater than or less than the starting value, respectively.

The second input is an `instructionlist`. The effect of `FOR` is to run that `instructionlist` repeatedly, assigning a new value to the control variable (the one named by the first member of the `forcontrol` list) each time. First the starting value is assigned to the control variable. Then the value is compared to the limit value. `FOR` is complete when the sign of (current-limit) is the same as the sign of the step size. (If no explicit step size is provided, the `instructionlist` is always run at least once. An explicit step size can lead to a zero-trip `FOR`, e.g., `FOR [I 1 0 1] ...`). Otherwise, the `instructionlist` is run, then the step is added to the current value of the control variable and `FOR` returns to the comparison step.

```
? for [i 2 7 1.5] [print :i]
2
3.5
5
6.5
?
```

See [RUN], page 69 .

do.while

`DO.WHILE instructionlist tfexpression (library procedure)`

command. Repeatedly evaluates the `instructionlist` as long as the evaluated `tfexpression` remains `TRUE`. Evaluates the first input first, so the `instructionlist` is always run at least once. The `tfexpression` must be an expressionlist whose value when evaluated is `TRUE` or `FALSE`.

while

`WHILE tfexpression instructionlist (library procedure)`

command. Repeatedly evaluates the `instructionlist` as long as the evaluated `tfexpression` remains `TRUE`. Evaluates the first input first, so the `instructionlist` may never be run at all. The `tfexpression` must be an expressionlist whose value when evaluated is `TRUE` or `FALSE`.

do.until

`DO.UNTIL instructionlist tfexpression (library procedure)`

command. Repeatedly evaluates the `instructionlist` as long as the evaluated `tfexpression` remains `FALSE`. Evaluates the first input first, so the `instructionlist` is always run at least once. The `tfexpression` must be an expressionlist whose value when evaluated is `TRUE` or `FALSE`.

until

UNTIL *tfexpression instructionlist* (library procedure)

command. Repeatedly evaluates the **instructionlist** as long as the evaluated **tfexpression** remains FALSE. Evaluates the first input first, so the **instructionlist** may never be run at all. The **tfexpression** must be an expressionlist whose value when evaluated is TRUE or FALSE.

case

CASE *value clauses* (library procedure)

command or operation. The second input is a list of lists (clauses); each clause is a list whose first element is either a list of values or the word ELSE and whose butfirst is a Logo expression or instruction. CASE examines the clauses in order. If a clause begins with the word ELSE (upper or lower case), then the butfirst of that clause is evaluated and CASE outputs its value, if any. If the first input to CASE is a member of the first element of a clause, then the butfirst of that clause is evaluated and CASE outputs its value, if any. If neither of these conditions is met, then CASE goes on to the next clause. If no clause is satisfied, CASE does nothing. Example:

```
to vowelp :letter
  output case :letter [ [[a e i o u] "true] [else "false] ]
end
```

cond

COND *clauses* (library procedure)

command or operation. The input is a list of lists (clauses); each clause is a list whose first element is either an expression whose value is TRUE or FALSE, or the word ELSE, and whose butfirst is a Logo expression or instruction. COND examines the clauses in order. If a clause begins with the word ELSE (upper or lower case), then the butfirst of that clause is evaluated and CASE outputs its value, if any. Otherwise, the first element of the clause is evaluated; the resulting value must be TRUE or FALSE. If it's TRUE, then the butfirst of that clause is evaluated and COND outputs its value, if any. If the value is FALSE, then COND goes on to the next clause. If no clause is satisfied, COND does nothing. Example:

```
to evens :numbers ; select even numbers from a list
  cond [ [[empty? :numbers] []]
        [[evenp first :numbers] ; assuming EVENP is defined
          [fput first :numbers evens butfirst :numbers]]
        [else evens butfirst :numbers] ]
end
```

8.2 Template-based Iteration

The procedures in this section are iteration tools based on the idea of a **template**. This is a generalization of an instruction list or an expression list in which **slots** are provided for the tool to insert varying data. Four different forms of template can be used.

The most commonly used form for a template is ‘**explicit-slot**’ form, or ‘**question mark**’ form. Example:

```
? show map [? * ?] [2 3 4 5]
[4 9 16 25]
?
```

In this example, the MAP tool evaluated the template `[? * ?]` repeatedly, with each of the members of the data list `[2 3 4 5]` substituted in turn for the question marks. The same value was used for every question mark in a given evaluation. Some tools allow for more than one datum to be substituted in parallel; in these cases the slots are indicated by `?1` for the first datum, `?2` for the second, and so on:

```
? show (map [(word ?1 ?2 ?1)] [a b c] [d e f])
[ada beb cfc]
?
```

If the template wishes to compute the datum number, the form `(? 1)` is equivalent to `?1`, so `(? ?1)` means the datum whose number is given in datum number 1. Some tools allow additional slot designations, as shown in the individual descriptions.

The second form of template is the ‘**named-procedure**’ form. If the template is a word rather than a list, it is taken as the name of a procedure. That procedure must accept a number of inputs equal to the number of parallel data slots provided by the tool; the procedure is applied to all of the available data in order. That is, if data `?1` through `?3` are available, the template `"PROC` is equivalent to `[PROC ?1 ?2 ?3]`.

```
? show (map "word [a b c] [d e f])
[ad be cf]
?
```

```
to dotprod :a :b ; vector dot product
op apply "sum (map "product :a :b)
end
```

The third form of template is ‘**named-slot**’ or ‘**lambda**’ form. This form is indicated by a template list containing more than one member, whose first member is itself a list. The first member is taken as a list of names; local variables are created with those names and given the available data in order as their values. The number of names must equal the number of available data. This form is needed primarily when one iteration tool must be used within the template list of another, and the `?` notation would be ambiguous in the inner template. Example:

```
to matmul :m1 :m2 [:tm2 transpose :m2] ; multiply two matrices
output map [[row] map [[col] dotprod :row :col] :tm2] :m1
end
```

The fourth form is ‘**procedure text**’ form, a variant of lambda form. In this form, the template list contains at least two members, all of which are lists. This is the form used by the `DEFINE` and `TEXT` primitives, and `APPLY` accepts it so that the text of a defined procedure can be used as a template.

Note: The fourth form of template is interpreted differently from the others, in that Logo considers it to be an independent defined procedure for the purposes of OUTPUT and STOP. For example, the following two instructions are identical:

```
? print apply [[x] :x+3] [5]
8
? print apply [[x] [output :x+3]] [5]
8
```

although the first instruction is in named-slot form and the second is in procedure-text form. The named-slot form can be understood as telling Logo to evaluate the expression `:x+3` in place of the entire invocation of `apply`, with the variable `x` temporarily given the value 5. The procedure-text form can be understood as invoking the procedure

```
to foo :x
  output :x+3
end
```

with input 5, but without actually giving the procedure a name. If the use of OUTPUT were interchanged in these two examples, we'd get errors:

```
? print apply [[x] output :x+3] [5]
Can only use output inside a procedure
? print apply [[x] [:x+3]] [5]
You don't say what to do with 8
```

The named-slot form can be used with STOP or OUTPUT inside a procedure, to stop the enclosing procedure.

The following iteration tools are extended versions of the ones in Appendix B of the book **Computer Science Logo Style, Volume 3: Advanced Topics** by Brian Harvey [MIT Press, 1987]. The extensions are primarily to allow for variable numbers of inputs.

apply

APPLY *template inputlist*

command or operation. Runs the "template," filling its slots with the members of *inputlist*. The number of members in *inputlist* must be an acceptable number of slots for *template*. It is illegal to apply the primitive TO as a template, but anything else is okay. APPLY outputs what *template* outputs, if anything.

See [TO], page 51 .

invoke

INVOKE *template input (library procedure)*
(INVOKE *template input1 input2 ...*)

command or operation. Exactly like APPLY except that the inputs are provided as separate expressions rather than in a list.

foreach

```
FOREACH data template (library procedure)
(FOREACH data1 data2 ... template)
```

command. Evaluates the template list repeatedly, once for each member of the data list. If more than one data list are given, each of them must be the same length. (The data inputs can be words, in which case the template is evaluated once for each character.

In a template, the symbol ?REST represents the portion of the data input to the right of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then ?REST would be replaced by [C D E]. If multiple parallel slots are used, then (?REST 1) goes with ?1, etc.

In a template, the symbol # represents the position in the data input of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then # would be replaced by 2.

map

```
MAP template data (library procedure)
(MAP template data1 data2 ...)
```

outputs a word or list, depending on the type of the data input, of the same length as that data input. (If more than one data input are given, the output is of the same type as data1.) Each member of the output is the result of evaluating the template list, filling the slots with the corresponding member(s) of the data input(s). (All data inputs must be the same length.) In the case of a word output, the results of the template evaluation must be words, and they are concatenated with WORD.

In a template, the symbol ?REST represents the portion of the data input to the right of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then ?REST would be replaced by [C D E]. If multiple parallel slots are used, then (?REST 1) goes with ?1, etc.

In a template, the symbol # represents the position in the data input of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then # would be replaced by 2.

See [WORD], page 9 .

map.se

```
MAP.SE template data (library procedure)
(MAP.SE template data1 data2 ...)
```

outputs a list formed by evaluating the template list repeatedly and concatenating the results using SENTENCE. That is, the members of the output are the members of the results of the evaluations. The output list might, therefore, be of a different length from that of the data input(s). (If the result of an evaluation is the empty list, it contributes nothing to the final output.) The data inputs may be words or lists.

In a template, the symbol ?REST represents the portion of the data input to the right of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then ?REST would be replaced by [C D E]. If multiple parallel slots are used, then (?REST 1) goes with ?1, etc.

In a template, the symbol # represents the position in the data input of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then # would be replaced by 2.

See [SENTENCE], page 9 .

filter

FILTER *tf*template data (library procedure)

outputs a word or list, depending on the type of the data input, containing a subset of the members (for a list) or characters (for a word) of the input. The template is evaluated once for each member or character of the data, and it must produce a TRUE or FALSE value. If the value is TRUE, then the corresponding input constituent is included in the output.

```
? print filter "vowelp "elephant
eea
?
```

In a template, the symbol ?REST represents the portion of the data input to the right of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then ?REST would be replaced by [C D E].

In a template, the symbol # represents the position in the data input of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then # would be replaced by 2.

find

FIND *tf*template data (library procedure)

outputs the first constituent of the data input (the first member of a list, or the first character of a word) for which the value produced by evaluating the template with that constituent in its slot is TRUE. If there is no such constituent, the empty list is output.

In a template, the symbol ?REST represents the portion of the data input to the right of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then ?REST would be replaced by [C D E].

In a template, the symbol # represents the position in the data input of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then # would be replaced by 2.

reduce

REDUCE template data (library procedure)

outputs the result of applying the template to accumulate the members of the data input. The template must be a two-slot function. Typically it is an associative function name like "SUM. If the data input has only one constituent (member in a list or character in a word), the output is that constituent. Otherwise, the template is first applied with ?1 filled with the next-to-last constituent and ?2 with the last constituent. Then, if there are more constituents, the template is applied with ?1 filled with the next constituent to the left and ?2 with the result from the previous evaluation. This process continues until all constituents have been used. The data input may not be empty.

Note: If the template is, like SUM, the name of a procedure that is capable of accepting arbitrarily many inputs, it is more efficient to use APPLY instead of REDUCE. The latter is good for associative procedures that have been written to accept exactly two inputs:

```
to max :a :b
  output ifelse :a > :b [:a] [:b]
end

print reduce "max [...]
```

Alternatively, REDUCE can be used to write MAX as a procedure that accepts any number of inputs, as SUM does:

```
to max [:inputs] 2
  if empty? :inputs ~
    [(throw "error [not enough inputs to max])]
  output reduce [ifelse ?1 > ?2 [?1] [?2]] :inputs
end
```

See [SUM], page 31 , [APPLY], page 78 .

crossmap**CROSSMAP template listlist (library procedure)**
(CROSSMAP template data1 data2 ...)

outputs a list containing the results of template evaluations. Each data list contributes to a slot in the template; the number of slots is equal to the number of data list inputs. As a special case, if only one data list input is given, that list is taken as a list of data lists, and each of its members contributes values to a slot. CROSSMAP differs from MAP in that instead of taking members from the data inputs in parallel, it takes all possible combinations of members of data inputs, which need not be the same length.

```
? show (crossmap [word ?1 ?2] [a b c] [1 2 3 4])
[a1 a2 a3 a4 b1 b2 b3 b4 c1 c2 c3 c4]
?
```

For compatibility with the version in the first edition of CSL¹, CROSSMAP templates may use the notation :1 instead of ?1 to indicate slots.

¹ Computer Science Logo Style

See [MAP], page 79 .

cascade

```
CASCADE endtest template startvalue (library procedure)
(CASCADE endtest tmp1 sv1 tmp2 sv2 ...)
(CASCADE endtest tmp1 sv1 tmp2 sv2 ... finaltemplate)
```

outputs the result of applying a template (or several templates, as explained below) repeatedly, with a given value filling the slot the first time, and the result of each application filling the slot for the following application.

In the simplest case, CASCADE has three inputs. The second input is a one-slot expression template. That template is evaluated some number of times (perhaps zero). On the first evaluation, the slot is filled with the third input; on subsequent evaluations, the slot is filled with the result of the previous evaluation. The number of evaluations is determined by the first input. This can be either a nonnegative integer, in which case the template is evaluated that many times, or a predicate expression template, in which case it is evaluated (with the same slot filler that will be used for the evaluation of the second input) repeatedly, and the CASCADE evaluation continues as long as the predicate value is FALSE. (In other words, the predicate template indicates the condition for stopping.)

If the template is evaluated zero times, the output from CASCADE is the third (startvalue) input. Otherwise, the output is the value produced by the last template evaluation.

CASCADE templates may include the symbol # to represent the number of times the template has been evaluated. This slot is filled with 1 for the first evaluation, 2 for the second, and so on.

```
? show cascade 5 [lput # ?] []
[1 2 3 4 5]
? show cascade [vowelp first ?] [bf ?] "spring
ing
? show cascade 5 [# * ?] 1
120
?
```

Several cascaded results can be computed in parallel by providing additional template-startvalue pairs as inputs to CASCADE. In this case, all templates (including the endtest template, if used) are multi-slot, with the number of slots equal to the number of pairs of inputs. In each round of evaluations, ?2 represents the result of evaluating the second template in the previous round. If the total number of inputs (including the first endtest input) is odd, then the output from CASCADE is the final value of the first template. If the total number of inputs is even, then the last input is a template that is evaluated once, after the end test is satisfied, to determine the output from CASCADE.

```
to fibonacci :n
output (cascade :n [?1 + ?2] 1 [?1] 0)
end

to piglatin :word
```

```

output (cascade [vowelp first ?] ~
  [word bf ? first ?] ~
  :word ~
  [word ? "ay])
end

```

cascade.2

CASCADE.2 *endtest temp1 startval1 temp2 startval2* (library procedure)

outputs the result of invoking **CASCADE** with the same inputs. The only difference is that the default number of inputs is five instead of three.

transfer

TRANSFER *endtest template inbasket* (library procedure)

outputs the result of repeated evaluation of the template. The template is evaluated once for each member of the list **inbasket**. **TRANSFER** maintains an **outbasket** that is initially the empty list. After each evaluation of the template, the resulting value becomes the new **outbasket**.

In the template, the symbol **?IN** represents the current member from the **inbasket**; the symbol **?OUT** represents the entire current **outbasket**. Other slot symbols should not be used.

If the first (*endtest*) input is an empty list, evaluation continues until all **inbasket** members have been used. If not, the first input must be a predicate expression template, and evaluation continues until either that template's value is **TRUE** or the **inbasket** is used up.

9 Macros

.macro

```
.MACRO procname :input1 :input2 ... (special form)
.DEFMACRO procname text
```

A macro is a special kind of procedure whose output is evaluated as Logo instructions in the context of the macro's caller. `.MACRO` is exactly like `TO` except that the new procedure becomes a macro; `.DEFMACRO` is exactly like `DEFINE` with the same exception.

Macros are useful for inventing new control structures comparable to `REPEAT`, `IF`, and so on. Such control structures can almost, but not quite, be duplicated by ordinary Logo procedures. For example, here is an ordinary procedure version of `REPEAT`:

```
to my.repeat :num :instructions
  if :num=0 [stop]
  run :instructions
  my.repeat :num-1 :instructions
end
```

This version works fine for most purposes, e.g.,

```
my.repeat 5 [print "hello]
```

But it doesn't work if the instructions to be carried out include `OUTPUT`, `STOP`, or `LOCAL`. For example, consider this procedure:

```
to example
  print [Guess my secret word. You get three guesses.]
  repeat 3 [type "|?? | ~
    if readword = "secret [pr "Right! stop]]
  print [Sorry, the word was "secret"!]
```

This procedure works as written, but if `MY.REPEAT` is used instead of `REPEAT`, it won't work because the `STOP` will stop `MY.REPEAT` instead of stopping `EXAMPLE` as desired.

The solution is to make `MY.REPEAT` a macro. Instead of actually carrying out the computation, a macro must return a list containing Logo instructions. The contents of that list are evaluated as if they appeared in place of the call to the macro. Here's a macro version of `REPEAT`:

```
.macro my.repeat :num :instructions
  if :num=0 [output []]
  output sentence :instructions ~
    (list "my.repeat :num-1 :instructions)
end
```

Every macro is an operation — it must always output something. Even in the base case, `MY.REPEAT` outputs an empty instruction list. To show how `MY.REPEAT` works, let's take the example

```
my.repeat 5 [print "hello]
```

For this example, MY.REPEAT will output the instruction list

```
[print "hello my.repeat 4 [print "hello]]
```

Logo then executes these instructions in place of the original invocation of MY.REPEAT; this prints **hello** once and invokes another repetition.

The technique just shown, although fairly easy to understand, has the defect of slowness because each repetition has to construct an instruction list for evaluation. Another approach is to make my.repeat a macro that works just like the non-macro version unless the instructions to be repeated include OUTPUT or STOP:

```
.macro my.repeat :num :instructions
catch "repeat.catchtag ~
  [op repeat.done runresult [repeat1 :num :instructions]]
op []
end

to repeat1 :num :instructions
if :num=0 [throw "repeat.catchtag]
run :instructions
.maybeoutput repeat1 :num-1 :instructions
end

to repeat.done :repeat.result
if empty? :repeat.result [op [stop]]
op list "output quoted first :repeat.result
end
```

If the instructions do not include STOP or OUTPUT, then REPEAT1 will reach its base case and invoke THROW. As a result, my.repeat's last instruction line will output an empty list, so the second evaluation of the macro result will do nothing. But if a STOP or OUTPUT happens, then REPEAT.DONE will output a STOP or OUTPUT instruction that will be re-executed in the caller's context.

The macro-defining commands have names starting with a dot because macros are an advanced feature of Logo; it's easy to get in trouble by defining a macro that doesn't terminate, or by failing to construct the instruction list properly.

Lisp users should note that Logo macros are NOT special forms. That is, the inputs to the macro are evaluated normally, as they would be for any other Logo procedure. It's only the output from the macro that's handled unusually.

Here's another example:

```
.macro localmake :name :value
output (list "local~
  word "" :name ~
  "apply ~
  ""make ~
```

```

      (list :name :value))
    end

```

It's used this way:

```

to try
  localmake "garply "hello
  print :garply
end

```

LOCALMAKE outputs the list

```
[local "garply apply "make [garply hello]]
```

The reason for the use of APPLY is to avoid having to decide whether or not the second input to MAKE requires a quotation mark before it. (In this case it would — MAKE "GARPLY "HELLO — but the quotation mark would be wrong if the value were a list.)

It's often convenient to use the ' function to construct the instruction list:

```

.macro localmake :name :value
  op '[local ,[word "" :name] apply "make [,:name] ,[:value]]]
end

```

On the other hand, ' is pretty slow, since it's tree recursive and written in Logo.

See [TO], page 51 , [DEFINE], page 52 , [APPLY], page 78 , [STOP], page 71 , [OUTPUT], page 71 .

.defmacro

See [dMACRO], page 85 .

macrop

```

MACROP name
MACRO? name

```

outputs TRUE if its input is the name of a macro.

macroexpand

```
MACROEXPAND expr (library procedure)
```

takes as its input a Logo expression that invokes a macro (that is, one that begins with the name of a macro) and outputs the the Logo expression into which the macro would translate the input expression.

```

.macro localmake :name :value
  op '[local ,[word "" :name] apply "make [,:name] ,[:value]]]
end

```

```
? show macroexpand [localmake "pi 3.14159]
```



```
[local "pi apply "make [pi 3.14159]]
```

10 Error Processing

If an error occurs, Logo takes the following steps. First, if there is an available variable named *ERRACT*, Logo takes its value as an instructionlist and runs the instructions. The operation *ERROR* may be used within the instructions (once) to examine the error condition. If the instructionlist invokes *PAUSE*, the error message is printed before the pause happens. Certain errors are "recoverable"; for one of those errors, if the instructionlist outputs a value, that value is used in place of the expression that caused the error. (If *ERRACT* invokes *PAUSE* and the user then invokes *CONTINUE* with an input, that input becomes the output from *PAUSE* and therefore the output from the *ERRACT* instructionlist.)

It is possible for an *ERRACT* instructionlist to produce an inappropriate value or no value where one is needed. As a result, the same error condition could recur forever because of this mechanism. To avoid that danger, if the same error condition occurs twice in a row from an *ERRACT* instructionlist without user interaction, the message "Erract loop" is printed and control returns to toplevel. "Without user interaction" means that if *ERRACT* invokes *PAUSE* and the user provides an incorrect value, this loop prevention mechanism does not take effect and the user gets to try again.

During the running of the *ERRACT* instructionlist, *ERRACT* is locally unbound, so an error in the *ERRACT* instructions themselves will not cause a loop. In particular, an error during a pause will not cause a pause-within-a-pause unless the user reassigns the value [*PAUSE*] to *ERRACT* during the pause. But such an error will not return to toplevel; it will remain within the original pause loop.

If there is no available *ERRACT* value, Logo handles the error by generating an internal *THROW "ERROR*. (A user program can also generate an error condition deliberately by invoking *THROW*.) If this throw is not caught by a *CATCH "ERROR* in the user program, it is eventually caught either by the toplevel instruction loop or by a pause loop, which prints the error message. An invocation of *CATCH "ERROR* in a user program locally unbinds *ERRACT*, so the effect is that whichever of *ERRACT* and *CATCH "ERROR* is more local will take precedence.

If a floating point overflow occurs during an arithmetic operation, or a two-input mathematical function (like *POWER*) is invoked with an illegal combination of inputs, the 'doesn't like' message refers to the second operand, but should be taken as meaning the combination.

See [*ERRACT*], page 91 , [*THROW*], page 71 , [*ERROR*], page 72 , [*CATCH*], page 71 , [*PAUSE*], page 72 , [*CONTINUE*], page 73 .

10.1 Error Codes

Here are the numeric codes that appear as the first member of the list output by *ERROR* when an error is caught, with the corresponding messages. Some messages may have two different codes depending on whether or not the error is recoverable (that is, a substitute value can be provided through the *ERRACT* mechanism) in the specific context. Some

messages are warnings rather than errors; these will not be caught. Errors 0 and 32 are so bad that Logo exits immediately.

- 0 Fatal internal error (can't be caught)
- 1 Out of memory
- 2 Stack overflow
- 3 Turtle out of bounds
- 4 PROC doesn't like DATUM as input (not recoverable)
- 5 PROC didn't output to PROC
- 6 Not enough inputs to PROC
- 7 PROC doesn't like DATUM as input (recoverable)
- 8 Too much inside ()'s
- 9 You don't say what to do with DATUM
- 10 ')' not found
- 11 VAR has no value
- 12 Unexpected ')'
- 13 I don't know how to PROC (recoverable)
- 14 Can't find catch tag for THROWTAG
- 15 PROC is already defined
- 16 Stopped
- 17 Already dribbling
- 18 File system error
- 19 Assuming you mean IFELSE, not IF (warning only)
- 20 VAR shadowed by local in procedure call (warning only)
- 21 Throw "Error
- 22 PROC is a primitive
- 23 Can't use TO inside a procedure
- 24 I don't know how to PROC (not recoverable)
- 25 IFTRUE/IFFALSE without TEST
- 26 Unexpected ']'
- 27 Unexpected '}'
- 28 Couldn't initialize graphics
- 29 Macro returned VALUE instead of a list
- 30 You don't say what to do with VALUE
- 31 Can only use STOP or OUTPUT inside a procedure
- 32 APPLY doesn't like BADTHING as input
- 33 END inside multi-line instruction
- 34 Really out of memory (can't be caught)

11 Special Variables

Logo takes special action if any of the following variable names exists. They follow the normal scoping rules, so a procedure can locally set one of them to limit the scope of its effect. Initially, no variables exist except for *ALLOWGETSET*, *CASEIGNOREDP*, and *UNBURYONEDIT*, which are TRUE and buried.

allowgetset

ALLOWGETSET (variable)

if TRUE, indicates that an attempt to use a procedure that doesn't exist should be taken as an implicit getter or setter procedure (setter if the first three letters of the name are SET) for a variable of the same name (without the SET if appropriate).

caseignoredp

CASEIGNOREDP (variable)

if TRUE, indicates that lower case and upper case letters should be considered equal by *EQUALP*, *BEFOREP*, *MEMBERP*, etc. Logo initially makes this variable TRUE, and buries it.

See [*EQUALP*], page 15 , [*BEFOREP*], page 15 , [*MEMBERP*], page 16 .

erract

ERRACT (variable)

an instructionlist that will be run in the event of an error. Typically has the value [*PAUSE*] to allow interactive debugging.

See [*PAUSE*], page 72 .

fullprintp

FULLPRINTP

if TRUE, then words that were created using backslash or vertical bar (to include characters that would otherwise not be treated as part of a word) are printed with the backslashes or vertical bars shown, so that the printed result could be re-read by Logo to produce the same value. If *FULLPRINTP* is TRUE then the empty word (however it was created) prints as `||`. (Otherwise it prints as nothing at all.)

loadnoisily

LOADNOISILY (variable)

if TRUE, prints the names of procedures defined when loading from a file (including the temporary file made by *EDIT*).

See [EDIT], page 64 .

printdepthlimit

PRINTDEPTHLIMIT (variable)

if a nonnegative integer, indicates the maximum depth of sublist structure that will be printed by PRINT, etc.

See [PRINT], page 21 .

printwidthlimit

PRINTWIDTHLIMIT (variable)

if a nonnegative integer, indicates the maximum number of members in any one list that will be printed by PRINT, etc.

See [PRINT], page 21 .

redefp

REDEFP (variable)

if TRUE, allows primitives to be erased (ERASE) or redefined (COPYDEF).

See [ERASE], page 60 , [COPYDEF], page 53 .

startup

STARTUP (variable)

if assigned a list value in a file loaded by LOAD, that value is run as an instructionlist after the loading.

See [LOAD], page 66 .

unburyonedit

UNBURYONEDIT (variable)

if TRUE, causes any procedure defined during EDIT or LOAD to be unburied, so that it will be saved by a later SAVE. Files that want to define and bury procedures must do it in that order.

See [EDIT], page 64 , See [LOAD], page 66 , See [SAVE], page 65 .

usealternatenames

USEALTERNATENAMES (variable)

if TRUE, causes Logo to generate non-English words (from the Messages file) instead of TRUE, FALSE, END, etc.

12 Internationalization

Berkeley Logo has limited support for non-English-speaking users. Alas, there is no Unicode support, and high-bit-on ASCII codes work in some contexts but not others.

If you want to translate Berkeley Logo for use with another language, there are three main things you have to do:

1. Primitive names
2. Error (and other) messages
3. Documentation

For primitive names, the easiest thing is to provide a startup file that defines aliases for the English primitive names, using COPYDEF:

```
COPYDEF "AVANT "FORWARD
```

This should take care of it, unless your language's name for one primitive is spelled like the English name of a different primitive. In that case you have to turn REDEFP on and be sure to copy the non-conflicting name before overwriting the conflicting one!

"Primitives" that are actually in the Logo library, of course, can just be replaced or augmented with native-language-named Logo procedures and filenames.

Of course Logo programs will still not look like your native language if the word order is dramatically different, especially if you don't put verbs before their objects.

For error messages, there is a file named Messages in the logolib directory with texts of messages, one per line. You can replace this with a file for your own language. Do not add, delete, or reorder lines; Logo finds messages by line number. The sequences %p, %s, and %t in these messages represent variable parts of the message and should not be translated. (%p PRINTs the variable part, while %s SHOWs it – that is, the difference is about whether or not brackets are shown surrounding a list. %t means that the variable part is a C text string rather than a Logo object.) If you want to change the order of two variable parts (no reorderable message has more than two), you would for example replace the line

```
%p doesn't like %s as input
```

with

```
%+s is a lousy input to %p
```

The plus sign tells the message printer to reverse the order; you must reverse the order of %p and %s, if both are used, to match. The plus sign goes just after the first percent sign in the message, which might not be at the beginning of the line. The sequence \n in a message represents a newline; don't be fooled into thinking that the "n" is part of the following word.

Some messages appear twice in the file; this isn't a mistake. The two spaces before "to" in "I don't know how to" aren't a mistake either. The message containing just "%p" is for user-provided error messages in THROW "ERROR. The message " in %s\n%s" is the part of all error messages that indicates where the error occurred if it was inside a procedure; you might want to change the word "in" to your language. "%s defined\n" is what LOAD prints

for each procedure defined if the variable `LOADNOISILY` is `TRUE`. `"to %p\nend\n\n"` is what `EDIT` puts in the temporary file if you ask to edit a procedure that isn't already defined.

Also in the Messages file are lines containing only one word each; the first of these is the word `"true"`. Some of these words are recognized by Logo in user input; some are generated by Logo; some are both. For example, the words `TRUE` and `FALSE` are recognized as Boolean values by `IF` and `IFELSE`, and are also generated by Logo as outputs from the primitive predicates such as `EQUALP`. The word `END` is recognized as the end of a procedure definition, and may be generated when Logo reconstructs a procedure body for `PO` or `EDIT`. I've used capital letters in this paragraph for easier reading, but the words in the Messages file should be in lower case.

If you replace these with non-English words, Logo will **recognize** both the English names and your alternate names. For example, if you replace the word `"true"` with `"vrai"` then Logo will understand both of these:

```
IF "TRUE [PRINT "YES]
IF "VRAI [PRINT "YES]
```

The variable `UseAlternateNames` determines whether Logo will **generate** other-language names – for example, whether predicate functions return the other-language alternates for `TRUE` and `FALSE`. This variable is `FALSE` by default, meaning that the English words will be generated.

You might wish to have English-named predicate functions generate English `TRUE` and `FALSE`, while other-language-named predicates generate the alternate words. This can be done by leaving `UseAlternateNames` false, and instead of defining the other-language predicates with `COPYDEF`, do it this way:

```
to french.boolean :bool
  if equalp :bool "true [output "vrai]
  if equalp :bool "false [output "faux]
  output :bool ; shouldn't happen
end

to make.french.predicate :french :english :arity
  define :french '[[[inputs] ,[:arity]]
    [output french.boolean
      apply ,[word "" :english] :inputs]]
end

? make.french.predicate "egal? "equal? 2
? pr egal? 3 4
faux
? pr egal? 4 4
vrai
? pr equal? 3 4
false
? pr equal? 4 4
true
```

The third input to `make.french.predicate` is the number of inputs that the predicate expects. This solution isn't quite perfect because the infix predicates (`=`, `<`, `>`) will still output in English. If you want them to generate alternate-language words, set `UseAlternateNames` to `TRUE` instead.

Some of the words in this section of the Messages file are names of Logo primitives (`OUTPUT`, `STOP`, `GOTO`, `TAG`, `IF`, `IFELSE`, `TO`, `.MACRO`). To translate these names, you must use `COPYDEF` as described earlier, in addition to changing the names in Messages. You should be consistent in these two steps. Don't forget the period in `".macro"`!

For documentation, there are two kinds: this manual and the help files. The latter are generated automatically from this manual if you have a Unix system, so in that case you need only translate this manual, maintaining the format. (The automatic helpfile generator notices things like capital letters, tabs, hyphens, and equal signs at the beginnings of lines.) The program `makefile.c` may require modification because a few of the primitive names are special cases (e.g., `LOG10` is the only name with digits included).

If you don't have Unix tools, you can just translate each helpfile individually. A period in a primitive name is represented as a `D` in the filename; there are no files for question marks because the `HELP` command looks for the file named after the corresponding primitive that ends in `P`.

INDEX

*

* 31

-

- 31

.

.defmacro 85
 .eq 16
 .macro 85
 .maybeoutput 73
 .setbf 13
 .setfirst 13
 .setitem 14
 .setsegmentsize 68

/

/ 31

=

= 15

'

' 74

+

+ 31

>

> 34

<

< 34

A

allopen 25
 allowgetset 91
 AllowGetSet 4
 and 37
 apply 78
 arc 41
 arctan 33
 arity 58

array 9
 array? 15
 arrayp 15
 arraytolist 10
 ascii 17
 ashift 36

B

back 39
 background 48
 backslashed? 16
 backslashedp 16
 before? 15
 beforep 15
 bf 11
 bfs 12
 bg 48
 bitand 35
 bitnot 36
 bitor 35
 bitxor 36
 bk 39
 bl 12
 buried 57
 buried? 62
 buriedp 62
 bury 61
 buryall 62
 buryname 62
 butfirst 11
 butfirsts 12
 butlast 12
 bye 73

C

cascade 82
 cascade.2 83
 case 76
 case-insensitive 6
 caseignoredp 91
 catch 71
 char 17
 clean 42
 clearscreen 42
 cleartext 28
 close 25
 closeall 25
 co 73
 combine 10
 comments 6

Computer_Science_Logo_Style	1
cond	76
contents	57
continue	73
copydef	53
Copyright	1
cos	33
count	17
crossmap	81
cs	42
ct	28
cursor	28

D

define	52
defined?	56
definedp	56
delimiters	6
dequeue	14
difference	31
do.until	75
do.while	75
dribble	26

E

ed	64
edall	65
edit	64
editfile	64
editor	64
edn	65
edns	65
edpl	65
edpls	65
edps	65
empty?	15
emptyp	15
eof?	27
eofp	27
epspict	49
equal?	15
equalp	15
er	60
erall	60
erase	60
erasefile	26
erf	26
ern	61
erns	61
erpl	61

erpls	61
erps	60
erract	91
error	72
errors	89
exp	32

F

fd	39
fence	43
file?	28
filep	28
fill	43
filter	80
find	80
first	11
firsts	11
for	74
foreach	79
forever	69
form	35
forward	39
fput	9
fs	44
fullprintp	91
fullscreen	44
fulltext	53

G

gc	67
gensym	10
getter	2
global	55
goto	74
gprop	55
greater?	34
greaterp	34

H

heading	41
help	66
hideturtle	42
home	41
ht	42

I

if	70
ifelse	70
iff	70
iffalse	70
ift	70
iftrue	70
ignore	74
int	32
invoke	78
isec	34
item	12

K

key?	28
keyp	28

L

label	43
last	11
leaving ucblgo	5
left	40
less?	34
lessp	34
line-continuation	6
list	9
list?	15
listp	15
listtoarray	10
ln	33
load	66
loadnoisily	91
loadpict	49
local	54
localmake	54
log10	32
logohelp	66
lowercase	18
lput	9
lshift	36
lt	40

M

macro?	87
macroexpand	87
macrop	87
make	54
map	79
map.se	79

mdarray	10
mditem	12
mdsetitem	13
member	17
member?	16
memberp	16
minus	31
modulo	32

N

name	54
name?	56
namelist	58
namep	56
names	57
nodes	58
nodribble	26
norefresh	45
not	37
number?	16
numberp	16

O

op	71
openappend	25
openread	24
openupdate	25
openwrite	25
or	37
output	71

P

palette	48
parse	18
pause	72
pc	48
pd	45
pe	46
pen	48
pencolor	48
pendown	45
pendown?	47
pendownp	47
penerase	46
penmode	47
penpaint	46
penpattern	48
penreverse	46
pensize	48

penup	46
pick	12
plist	55
plist?	56
plistp	56
plists	57
plist	58
po	58
poall	59
pon	59
pons	59
pop	14
popl	59
popls	59
pops	59
pos	41
pot	60
pots	60
power	32
pprop	55
ppt	46
pr	21
prefix	24
primitive?	56
primitivep	56
print	21
printdepthlimit	92
printwidthlimit	92
procedure?	56
procedurep	56
procedures	57
product	31
pu	46
push	14
px	46

Q

queue	14
quoted	13
quotient	31

R

radarctan	33
radcos	33
radsin	33
random	34
rawascii	17
rc	23
rcl	23
readchar	23

readchars	23
reader	27
readlist	22
readpos	27
readrawline	23
readword	22
redefp	92
reduce	80
refresh	44
remainder	32
remdup	13
remove	12
remprop	55
repcount	70
repeat	69
rerandom	35
reverse	10
right	40
rl	22
round	32
rseq	34
rt	40
run	69
runparse	19
runparsing	6
runresult	69
rw	22

S

save	65
savel	66
savepict	48
screenmode	45
scrunch	42
scrunch.dat	44
se	9
sentence	9
setbackground	47
setbg	47
setcursor	28
seteditor	67
seth	40
setheading	40
sethelploc	67
setitem	13
setlibloc	67
setmargins	29
setpalette	46
setpc	46
setpen	47
setpencolor	46

setpenpattern	47
setpensize	47
setpos	40
setprefix	24
setread	26
setreadpos	27
setscrunch	44
settc	29
settemploc	67
setter	2
settextcolor	29
setwrite	26
setwritepos	27
setx	40
setxy	40
sety	40
shell	23
show	22
shown?	45
shownp	45
showturtle	42
sin	33
splitscreen	44
sqrt	32
ss	44
st	42
standout	18
starting ucblgo	5
startup	92
step	63
stepped	57
stepped?	64
steppedp	64
stop	71
substring?	16
substringp	16
sum	31

T

tag	74
temp	64
template	76
test	70
text	53

textscreen	43
thing	54
throw	71
to	51
towards	41
trace	63
traced	57
traced?	63
tracedp	63
transfer	83
ts	43
turtlemode	45
type	21

U

unbury	62
unburyall	62
unburyname	62
unburyonedit	92
unstep	63
until	75
untrace	63
uppercase	18
usealternatenames	92

W

wait	73
while	75
window	43
word	9
wordp	15
wrap	42
writepos	27
writer	27

X

xcor	41
------	----

Y

ycor	41
------	----

Short Contents

1	Introduction	1
2	Data Structure Primitives	9
3	Communication	21
4	Arithmetic	31
5	Logical Operations	37
6	Graphics	39
7	Workspace Management	51
8	Control Structures	69
9	Macros	85
10	Error Processing	89
11	Special Variables	91
12	Internationalization	95
	INDEX	99

Table of Contents

1	Introduction	1
1.1	Overview	1
1.2	Getter/Setter Variable Syntax	2
1.3	Entering and Leaving Logo	5
1.4	Tokenization	6
2	Data Structure Primitives	9
2.1	Constructors	9
	word	9
	list	9
	sentence	9
	fput	9
	lput	9
	array	9
	mdarray	10
	listtoarray	10
	arraytolist	10
	combine	10
	reverse	10
	gensym	10
2.2	Data Selectors	11
	first	11
	firsts	11
	last	11
	butfirst	11
	butfirsts	12
	butlast	12
	item	12
	mditem	12
	pick	12
	remove	12
	remdup	13
	quoted	13
2.3	Data Mutators	13
	setitem	13
	mdsetitem	13
	.setfirst	13
	.setbf	13
	.setitem	14
	push	14
	pop	14
	queue	14
	dequeue	14

2.4	Predicates	14
	wordp	15
	listp	15
	arrayp	15
	empty	15
	equalp	15
	beforep	15
	.eq	16
	memberp	16
	substringp	16
	numberp	16
	backslashedp	16
2.5	Queries	17
	count	17
	ascii	17
	rawascii	17
	char	17
	member	17
	lowercase	18
	uppercase	18
	standout	18
	parse	18
	runparse	19
3	Communication	21
3.1	Transmitters	21
	print	21
	type	21
	show	22
3.2	Receivers	22
	readlist	22
	readword	22
	readrawline	23
	readchar	23
	readchars	23
	shell	23
3.3	File Access	24
	setprefix	24
	prefix	24
	openread	24
	openwrite	25
	openappend	25
	openupdate	25
	close	25
	allopen	25
	closeall	25
	erasefile	26
	dribble	26

	nodribble	26
	setread	26
	setwrite	26
	reader	27
	writer	27
	setreadpos	27
	setwritepos	27
	readpos	27
	writepos	27
	eofp	27
	filep	28
3.4	Terminal Access	28
	keyp	28
	cleartext	28
	setcursor	28
	cursor	28
	setmargins	29
	setttextcolor	29
4	Arithmetic	31
4.1	Numeric Operations	31
	sum	31
	difference	31
	minus	31
	product	31
	quotient	31
	remainder	32
	modulo	32
	int	32
	round	32
	sqrt	32
	power	32
	exp	32
	log10	32
	ln	33
	sin	33
	radsin	33
	cos	33
	radcos	33
	arctan	33
	radarctan	33
	iseq	34
	rseq	34
4.2	Numeric Predicates	34
	lessp	34
	greaterp	34
4.3	Random Numbers	34
	random	34

	rerandom	35
4.4	Print Formatting	35
	form	35
4.5	Bitwise Operations	35
	bitand	35
	bitor	35
	bitxor	36
	bitnot	36
	ashift	36
	lshift	36
5	Logical Operations	37
	and	37
	or	37
	not	37
6	Graphics	39
6.1	Turtle Motion	39
	forward	39
	back	39
	left	40
	right	40
	setpos	40
	setxy	40
	setx	40
	sety	40
	setheading	40
	home	41
	arc	41
6.2	Turtle Motion Queries	41
	pos	41
	xcor	41
	ycor	41
	heading	41
	towards	41
	scrunch	42
6.3	Turtle and Window Control	42
	showturtle	42
	hideturtle	42
	clean	42
	clearscreen	42
	wrap	42
	window	43
	fence	43
	fill	43
	label	43
	textscreen	43
	fullscreen	44

	splitscreen	44
	setscrunch	44
	refresh	44
	norefresh	45
6.4	Turtle and Window Queries	45
	shownp	45
	screenmode	45
	turtlemode	45
6.5	Pen and Background Control	45
	pendown	45
	penup	46
	penpaint	46
	penerase	46
	penreverse	46
	setpencolor	46
	setpalette	46
	setpensize	47
	setpenpattern	47
	setpen	47
	setbackground	47
6.6	Pen Queries	47
	pendownp	47
	penmode	47
	pencolor	48
	palette	48
	pensize	48
	pen	48
	background	48
6.7	saving and loading pictures	48
	savepict	48
	loadpict	49
	eps pict	49
7	Workspace Management	51
7.1	Procedure Definition	51
	to	51
	define	52
	text	53
	fulltext	53
	copydef	53
7.2	Variable Definition	53
	make	54
	name	54
	local	54
	localmake	54
	thing	54
	global	55
7.3	Property Lists	55

	pprop	55
	gprop	55
	remprop	55
	plist	55
7.4	Workspace Predicates	56
	procedurep	56
	primitivep	56
	definedp	56
	namep	56
	plistp	56
7.5	Workspace Queries	57
	contents	57
	buried	57
	traced	57
	stepped	57
	procedures	57
	names	57
	plists	57
	namelist	58
	plist	58
	arity	58
	nodes	58
7.6	Workspace Inspection	58
	po	58
	poall	59
	pops	59
	pons	59
	popls	59
	pon	59
	popl	59
	pot	60
	pots	60
7.7	Workspace Control	60
	erase	60
	erall	60
	erps	60
	erns	61
	erpls	61
	ern	61
	erpl	61
	bury	61
	buryall	62
	buryname	62
	unbury	62
	unburyall	62
	unburyname	62
	buriedp	62
	trace	63

untrace.....	63
tracedp.....	63
step.....	63
unstep.....	63
steppedp.....	64
edit.....	64
editfile.....	64
edall.....	65
edps.....	65
edns.....	65
edpls.....	65
edn.....	65
edpl.....	65
save.....	65
savel.....	66
load.....	66
help.....	66
seteditor.....	67
setlibloc.....	67
sethelploc.....	67
settemploc.....	67
gc.....	67
.setsegmentsize.....	68

8 Control Structures..... 69

8.1 Control.....	69
run.....	69
runresult.....	69
repeat.....	69
forever.....	69
repcount.....	70
if.....	70
ifelse.....	70
test.....	70
iftrue.....	70
iffalse.....	70
stop.....	71
output.....	71
catch.....	71
throw.....	71
error.....	72
pause.....	72
continue.....	73
wait.....	73
bye.....	73
.maybeoutput.....	73
goto.....	74
tag.....	74

ignore	74
'	74
for	74
do.while	75
while	75
do.until	75
until	75
case	76
cond	76
8.2 Template-based Iteration	76
apply	78
invoke	78
foreach	79
map	79
map.se	79
filter	80
find	80
reduce	80
crossmap	81
cascade	82
cascade.2	83
transfer	83
9 Macros	85
.macro	85
.defmacro	87
macrop	87
macroexpand	87
10 Error Processing	89
10.1 Error Codes	89
11 Special Variables	91
allowgetset	91
caseignoredp	91
erract	91
fullprintp	91
loadnoisily	91
printdepthlimit	92
printwidthlimit	92
redefp	92
startup	92
unburyonedit	92
usealternatenames	92
12 Internationalization	95

INDEX	99
-------------	----

